

INPUTS

8 HDMI: On female HDMI connectors

OUTPUTS

8 HDMI: On female HDMI connectors

PORTS

1 Ethernet: On an RJ-45 connector

1 RS-232: On a 3-pin terminal block connector

1 USB: On a USB type A connector, for powering an external device

1 USB: On a mini USB connector, for firmware upgrade or communication with a PC or serial controller

VIDEO

HDMI Support: Deep Color, 3D, ARC, up to 7.1 uncompressed audio channels as specified in HDMI 2.0

Content Protection: HDCP 2.2

Max. Output Resolution: 4K@60Hz (4:4:4)

USER INTERFACE

Control: Input/output selection, mute, test pattern, memory, front panel lock, buttons. RS-232 serial commands transmitted by a PC, touch screen system or other serial controller, embedded web pages via LAN for configuration and control

Indicators: Input/output LCD display

POWER

Source: 100–240V AC 50/60Hz

Consumption: 600mA

ENVIRONMENTAL CONDITIONS

Operating Temperature: 0° to +40°C (32° to 104°F)

Storage Temperature: –40° to +70°C (–40° to 158°F)

Humidity: 10% to 90%, RH (non-condensing)

ACCESSORIES

Included: Rack ears, rubber feet, power cord

PRODUCT DIMENSION

43.64cm x 18.30cm x 4.36cm (17.18" x 7.20" x 1.72") W, D, H

PRODUCT WEIGHT

2.4kg (5.2lbs) approx.

SHIPPING DIMENSION

52.50cm x 33.00cm x 10.70cm (20.67" x 12.99" x 4.21") W, D, H

SHIPPING WEIGHT

3.3kg (7.3lbs) approx.
