



Corvid 44 12G

Take command of the most challenging projects using the immense power of the newest member of the Corvid product line. Corvid 44 12G is AJA's blazingly fast, compact 8-lane PCIe 3.0 I/O card with four bidirectional 12G-SDI HD-BNC connections, designed for today's most demanding video and audio workflows. Corvid 12G 44 is available in several configurations, including full-height or low-profile, with passive or active cooling.

Whether you are working with HFR 8K/4K/UltraHD, 2K/HD, SD, Deep Color and/or HDR, experience the quality and peace of mind that Corvid 44 12G brings to your projects. Supporting 10-bit 4:2:2 and 4:4:4, at up to 12-bit color spaces, Corvid 44 12G offers ingest and output over 12G-SDI, which is also backwards compatible with 6G-SDI, 3G-SDI, and 1.5G-SDI. The bidirectional 12G-SDI ports provide immense flexibility for capture and simultaneous pass-through for a range of solutions.

Video Formats

- (8K) 8192 x 4320p 23.98, 24, 25, 29.97, 30, 47.95, 48, 50, 59.94, 60
- (UHD2) 7680 x 4320p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- (4K) 4096 x 2160p 23.98, 24, 25, 29.97, 30, 47.95, 48, 50, 59.94, 60
- (UltraHD) 3840 x 2160p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- (2K) 2048 x 1080p 23.98, 24, 25, 29.97, 30, 47.95, 48, 50, 59.94, 60
- (2K) 2048 x 1080PsF 23.98, 24, 25, 29.97, 30
- (HD) 1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- (HD) 1080PsF 23.98, 24, 25, 29.97, 30
- (HD) 1080i 50, 59.94, 60
- (HD) 720p 50, 59.94, 60
- (SD) 625i 50
- (SD) 525i 59.94

Note: High Frame Rate capabilities are dependent on host system attributes. Not all systems and configurations will support all frame rates.

Video Inputs Digital

- 12G-SDI, SMPTE-2082, 12-bit, 10-bit and 8-bit
- 6G-SDI, SMPTE-2081, 10-bit and 8-bit
- 3G-SDI, SMPTE-259/292/296/424/425, 12-bit, 10-bit and 8-bit
- 4K/UltraHD 4:4:4 (4x BNC)
- 1.5G-SDI, SMPTE 372M, Dual Link HD 4:4:4 (2x BNC), 12-bit, 10-bit and 8-bit

bit

- 1.5G-SDI, SMPTE 292M, Single Link 4:2:2 (1x BNC), 10-bit and 8-bit

Note: Corvid 44 12G SDI connectors are HD BNC

Video Outputs Digital

- 12G-SDI, SMPTE-2082, 12-bit, 10-bit and 8-bit
- 6G-SDI, SMPTE-2081, 10-bit and 8-bit
- 3G-SDI, SMPTE-259/292/296/424, 12-bit, 10-bit and 8-bit
- 4K/UltraHD 4:4:4 (4x BNC)
- 1.5G-SDI, SMPTE 372M, Dual Link HD 4:4:4 (2x BNC), 12-bit, 10-bit and 8-bit
- 1.5G-SDI, SMPTE 292M, Single Link 4:2:2 (1x BNC), 10-bit and 8-bit

Note: Corvid 44 12G SDI connectors are HD BNC

SDI I/O

- SDI connections are bidirectional
 - 2K/HD, capture and monitoring is simultaneous
 - 4K/UltraHD with 12G-SDI, capture and monitoring is simultaneous.
 - 4K/UltraHD with 3G-SDI, all four connections must be used for either Input or Output.

- o 8K/UHD2 with 12G-SDI, connections must be used for either Input or Output.

Note: When connections are configured for 12G-SDI or 6G-SDI, only UltraHD/4K/UHD2/8K formats are supported.

Audio Inputs Digital

- 16-channel, 24 and 16-bit SDI embedded audio, 48 kHz sample rate, synchronous

Audio Outputs Digital

- 16-channel, 24-bit SDI embedded audio, 48 kHz sample rate, synchronous

Downstream Keyer

- Supports graphics with alpha channel over video, matte or framebuffer, or framebuffer content over incoming video or matte up to UltraHD/4K

Reference

- Analog Color Black (1V) or Composite Sync (2 or 4V) or HD Tri-Level Sync (1V) via 1x HD-BNC on PCIe bracket
- Reference input is terminated into 75 ohms when Genlock is set to Ref In

Timecode

- LTC timecode input via 2-pin header on PCIe card [both short (low profile) and tall (full height) models]
- LTC timecode input via HD-BNC Ref In connector (switchable) on PCIe bracket [tall (full height) models only]

Electrical Interface

- 8-lane PCIe 3.0

Machine Controls

- RS-422, Sony 9-pin protocol via header on PCIe card [both short (low profile) and tall (full height) models]
- RS-422, Sony 9-pin protocol via port on PCIe bracket connected to header via DB9 cable [tall (full height) models only]
- 9-pin D-connector pinout is as follows:

1	GND
2	RX-
3	TX+
4	GND
5	No Connection
6	GND
7	RX+
8	TX-
9	GND
Shell	GND

Noise

- <50dBA (A-weighted at 1m in free air) [models with active cooling (fan)]
- Ultra quiet (virtually silent) [models with passive* cooling (no fan)]
- Passive cooling requires in-host/chassis air-flow minimum of 150 LFM (linear feet per minute) at 30 C

Size (w x d x h)

- 0.75" x 7.0" x 3.15" (19 x 178 x 80 mm) [short (low profile) models]
- 0.75" x 7.0" x 4.75" (19 x 178 x 121 mm) [tall (full height) models]

Weight

- PCIe Card: 0.6 lbs (0.3 kg)
- Cables (all combined): 0.6 lbs (0.3 kg)

Power

- 25W typical, 32W maximum
- PC Internal ATX Power Connector (Molex p/n 45559-0002)

Note: Unlike other Corvid cards, Corvid 44 12G can use either PCIe power from a 6 pin ATX connector, or via the PCIe slot.

Environment

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)