



## OG-ROI-DVI

### Video Input Formats

- Computer Signals:
  - WUXGA (1920 x 1200) 60 Hz max
  - VGA (640 x 480) minimum
- Video Signals:
  - (HD) 1920 x 1080i 50, 59.94
  - (HD) 1920 x 1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
  - (HD) 1280 x 720p 50, 59.94, 60
  - (SD) 625i, 525i
  - (SD) 580p, 480p

**Note:** Frame rates limited by the 166 mHz max pixel rate of the DMI receiver.

### Video Output Formats

- (HD) 1920 x 1080p 50, 59.94, 60, SMPTE 425-1 Level A mapping structure 1 (4:2:2 10-bit YCbCr)
- (HD) 1920 x 1080p 23.98, 24, 25, 29.97, 30
- (HD) 1920 x 1080i 50, 59.94, 60
- (HD) 1280 x 720p 50, 59.94, 60
- (SD) 625i 25
- (SD) 525i 29.97

### Color Range

- Full
- SMPTE

### Reference Source

- Free Run
- Card Ext Ref
- OG Frame Ref 1

- OG Frame Ref 2

### Reference Input

- Supported reference video inputs include:
  - 1080i tri-level sync
  - 1080p tri-level sync
  - 720p tri-level sync
  - 625i Color Black
  - 525i Color Black
- 75 ohm terminating

### Video Input

- 1x DVI input connector (with embedded audio, up to 8-channels)

### Video Outputs

- DVI
  - 1x HDMI loop through connector (with embedded audio, up to 8-channels)
- SDI
  - 3G-SDI, SMPTE-259/292/424, 1x BNC

### Audio Inputs

- 2-channel balanced analog audio inputs, 2x 3-pin terminal blocks connectors

### Audio Output

- SDI embedded audio, 24-bit, 2-channel or 8-channel

### User Interface



- openGear DashBoard network control software via Windows, macOS or Linux

## Size (w x d x h)

---

- openGear standard form factor, front slot and rear card. Two slots required for each card

## Weight

---

- 0.5 lb (0.3 kg)

## Power

---

- openGear frame compatible, 12.0 watts max per card

## Environment

---

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)