

A-NeuVideo ANI-41STREAM UHD 4x1 Multi-input to HDBaseT and Live Video Streaming Transmitter with Recording

- **HDMI Bandwidth:** 10.2Gbps
- **DisplayPort Bandwidth:** 10.2Gbps
- **USB-C Bandwidth:** 10.2Gbps
- **VGA Bandwidth:** 165MHz
- **HDBaseT™ Bandwidth:** 10.2Gbps
- **Input Ports:**
 - HDMI (Type-A)
 - DisplayPort
 - USB (Type-C)
 - VGA (HD-15)
 - Analog Stereo (3.5mm)
- **Output Port:** HDBaseT™ (RJ-45)
- **Control/Streaming Port:** LAN (RJ-45)
- **Pass-through Ports:**
 - IR Extender (3.5mm)
 - IR Blaster (3.5mm)
 - RS-232 (4-pin Terminal Block)
- **Control Ports:**
 - RS-232 (4-pin Terminal Block)
 - Trigger (10-pin Terminal Block)
- **Service Port:** USB 2.0 (Type-A)
- **IR Frequency:** 30 ~ 50kHz (30 ~ 60kHz under ideal conditions)
- **Baud Rate:** 19200 (Control) Up to 115200 (Bypass)
- **Power Supply:** 24V/3.75A DC (US/EU standards, CE/FCC/UL certified)
- **ESD Protection:** Human Body Model:
 - ±12kV (Air Discharge)
 - ±8kV (Contact Discharge)
- **Dimensions (WxHxD):** 9.1 x 1 x 5.9 in (231.5x25x150mm) [Case Only] / 9.1 x 1 x 6.1 in (231.5x25x158mm) [All Inclusive]
- **Weight:** 2 lbs / 909g
- **Chassis Material:** Metal (Steel)
- **Chassis Color:** Black
- **Operating Temperature:** 0°C - 40°C/32°F - 104°F
- **Storage Temperature:** -20°C - 60°C/-4°F - 140°F
- **Relative Humidity:** 20 - 90% RH (Non-condensing)
- **Power Consumption:** 39.84W