

Panel	Panel Type:	LED-Backlit TFT LCD (IPS Technology)
	Panel Size:	31.5"
	Max. Resolution:	FHD 1920 x 1080
	Pixel Pitch:	0.364 mm
	Brightness:	350 cd/m ²
	Contrast Ratio:	20,000,000:1 (DCR)
	Viewing Angle (H/V):	178°/178°
	Display Colour:	16.7M
	Response Time:	5 ms
	Surface Treatment:	Anti-Glare Treatment (Haze <2%), 3H Hard Coating
Frequency	Frequency (H):	31 kHz-92 kHz
	Frequency (V):	48 Hz-85 Hz
Signal Input	HDMI:	1.3b x 1
	DVI:	24-Pin DVI-D
	VGA:	15-Pin D-Sub x 1
	Component:	RCA x 1
	Composite:	RCA x 1 (Share with Component-Y)
External Control	IR In:	3.5 mm Phone Jack
	IR Out:	3.5 mm Phone Jack
	RS232 In:	2.5 mm Phone Jack
	RS232 Out:	2.5 mm Phone Jack
	LAN:	RJ45 x 1
Other Connectivity	USB:	2.0 x 1 (Service Port / Media Playback)
Audio	Audio In:	Stereo Audio Jack (3.5 mm), Stereo Audio Jack (RCA)
	Audio Out:	Stereo Audio Jack (RCA)
	Internal Speakers:	10W x 2
Power	Power Supply:	Internal
	Power Requirements:	AC 100-240V, 50/60 Hz
	On Mode:	50W (On)
	Stand-by Mode:	< 0.5W
	Off Mode:	< 0.5W
Operating Conditions	Temperature:	0°C-40°C (32°F-104°F)
	Humidity:	20%-80%(non-condensing)
Storage Conditions	Temperature:	-20°C-60°C (-4°F-140°F)
	Humidity:	5%-90% (non-condensing)

Mounting	VESA FPMPI:	Yes (200 x 200 mm & 100 x 100 mm)
Security	Kensington Security Slot:	Yes
Dimensions	Product w/o Base (W x H x D):	726.5 x 425.4 x 65.1 mm (28.6" x 16.7" x 2.6")
	Packaging (W x H x D):	818.0 x 547.0 x 139.0 mm (32.2" x 21.5" x 5.5")
Weight	Product w/o Base:	5.2 kg (11.5 lb)
	Packaging:	7.8 kg (17.2 lb)
Regulation Approval	Certifications & Compliance:	FCC, CE, CB, WEEE, RoHS, REACH,EAC
Accessories	Supplied:	Power Cord, VGA Cable, RS232 Cable, Remote Control, Batteries, CD
Optional Accessories	Ceiling Mount (Landscape only):	CMP-01+LMK-02, CMP-01+WMK-03
	Wall Mount (Landscape only):	WMA-01, LMA-01, LMK-02, WMK-01, WMK-03, PMK-01
	Desk mount (Landscape only):	DMC-01, ES-02
	Stand:	STD-06