

<b>Panel</b>	Panel Type:	LED-Backlit TFT LCD (TN Technology)
	Panel Size:	19.0"
	Max. Resolution:	SXGA 1280 x 1024
	Pixel Pitch:	0.294 mm
	Brightness:	250 cd/m <sup>2</sup>
	Contrast Ratio:	20,000,000:1 (DCR)
	Viewing Angle (H/V):	170°/160°
	Display Colour:	16.7M
	Response Time:	3 ms
<b>Frequency</b>	Frequency (H):	24 kHz-83 kHz
	Frequency (V):	50 Hz-75 Hz
<b>Signal Input</b>	DisplayPort:	x 1
	HDMI:	1.4 x 1
	DVI:	24-Pin DVI-D
	VGA:	15-Pin D-Sub x 1
<b>Audio</b>	Audio In:	Stereo Audio Jack (3.5 mm)
	Internal Speakers:	2W x 2
	Power Supply:	External
	Power Requirements:	DC 12V, 1.72A
	On Mode:	15W (On)
	Stand-by Mode:	< 0.5W
	Off Mode:	< 0.5W
	Thickness:	3.0 mm (0.12")
	Reflection Rate:	< 1%
	Transmission Rate:	> 97%
	Hardness:	> 9H
<b>Operating Conditions</b>	Temperature:	0°C-40°C (32°F-104°F)
	Humidity:	10%-90% (non-condensing)
<b>Storage Conditions</b>	Temperature:	-20°C-60°C (-4°F-140°F)
	Humidity:	5%-95% (non-condensing)
<b>Mounting</b>	VESA FPMPI:	Yes (100 x 100 mm & 75 x 75 mm)
<b>Stand</b>	Tilt:	0° to 22°
<b>Security</b>	Kensington Security Slot:	Yes
<b>Dimensions</b>	Product with Base (W x H x D):	445.4 x 420.2 x 175.0 mm (17.5" x 16.5" x 6.9")
	Product w/o Base (W x H x D):	445.4 x 383.9 x 64.5 mm (17.5" x 15.1" x 2.5")
	Packaging (W x H x D):	552.0 x 526.0 x 225.0 mm (21.7" x 20.7" x 8.9")

<b>Weight</b>	Product w/o Base:	6.0 kg (13.2 lb)
	Product with Base:	6.8 kg (15.0 lb)
	Packaging:	8.5 kg (18.7 lb)
<b>Regulation Approval</b>	Certifications & Compliance:	LVD, CE, RoHS, WEEE, REACH, EAC, FCC
<b>Accessories</b>	Supplied:	Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card
<b>Optional Accessories</b>	Ceiling Mount (Landscape only):	<u><a href="#">CMP-01+WMK-03</a></u>
	Wall Mount (Landscape only):	<u><a href="#">WMA-01</a></u> , <u><a href="#">WMK-01</a></u>
	Desk mount (Landscape only):	<u><a href="#">DMC-01</a></u> , <u><a href="#">DMC-02D</a></u> , <u><a href="#">DMS-01D</a></u> , <u><a href="#">DMS-01Q</a></u> , <u><a href="#">ES-02</a></u>