

Bolide BN-2600ACTC Access Control Camera with Face Recognition and Temperature Indicator

| Hardware | |
|--------------------------|---|
| System | Linux operation system |
| RAM | 16G EMMC |
| Image sensor | 1/2.7" CMOS |
| Lens | 4mm |
| Camera parameters | |
| Effective pixel | 2MP, 1920*1080 |
| Min. Lux | Color 0.01Lux @F1.2 (ICR) B/W 0.001Lux @F1.2 |
| SNR | ≥50db(AGC OFF) |
| WDR | ≥80db |
| Face recognition | |
| Height | 1.2 - 2.2, angle adjustable |
| Distance | 0.5 - 3 meters |
| View angle | Vertical ±30° |
| Reco. Time | <500ms |
| Function | Support 22400 faces database and 100000 records |
| Temperature | |
| Range | 30-45 °C |
| Accuracy | ±0.3 °C |
| Distance | 0.3 - 0.8 meters |
| Response time | <300ms |
| Interface | |
| Internal interface | RJ45 10M/100M Ethernet |
| Weigand port | Support input/output 26 and 34 |
| Alarm output | 1ch relay output |
| USB port | 1 USB port (can be connected to ID identifier) |
| General | |
| Power input | DC 12V/3A |
| Power consumption | 20W(MAX) |
| Working temperature | 0°C ~ 50°C |
| Humidity | 5 ~ 90%, no condense |
| Dimension | 154mm (W) * 89mm (H) * 361.4mm (L) |
| Weight | 2.1kg |