INPUTS

1 CAT: On an RJ–45 female connector for extension line (PT–2UR)

1 Stereo Analog Unbalanced Audio: On a 3.5mm mini jack connector for audio extension (PT–2UT)

OUTPUTS

1 CAT: On an RJ–45 female connector for extension line (PT–2UT)

1 Stereo Analog Unbalanced Audio: On a 3.5mm mini jack connector for audio extension (PT–2UR)

PORTS

1 USB: On a USB–B female connector for USB host extension (PT–2UT)

4 USB: On USB–A female connectors for USB devices extension (PT–2UR)

1 RS–232: On a 3–pin terminal block connector for serial link extension

EXTENDED USB

Data Rate: Up to 480Mbps

Transmitted Data Bandwidth: Up to 300Mbps

Standards Compliance: 1.1 and 2.0 USB

EXTENSION LINE

Reach Using Shielded UNIKAT Cables: Up to 100m (330ft)

Reach Using CAT 5e Cables: Up to 30m (100ft)

EXTENDED RS-232

Baud Rate: 9600

PT-2UR USB CHARGING

Max Total Current When PSU–Powered: 3A

Max Current Per Port When PSU–Powered: 2A

Max Total/Per–port Current When PoC–Powered: 0.5A

USER INTERFACE

Indicators: LINK and ON LEDs

POWER

Source: 12V DC, 2A

Consumption: 500mA

ENCLOSURE

Size: Pico Tools

Type: Aluminum

Cooling: Convection ventilation

ACCESSORIES

Includes: 1 12V power–supply, 1 C–USB/AB–6 USB type–A male to USB type–B male 2m cable

PRODUCT DIMENSIONS

6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H

PRODUCT WEIGHT

0.2kg (0.5lbs) approx.

SHIPPING DIMENSIONS

15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

SHIPPING WEIGHT

0.7kg (1.5lbs) approx.