

Technical

AV Inputs: 2x HDMI, 1x Display Port, 1x VGA

AV Outputs: 1x HDBaseT RJ45, 1x HDMI, 1x Analog Audio on 6-pin terminal block, 1x Digital Audio on PCM RCA

DDC Signal (Data): Input DDC Signal: 5 Volts p-p (TTL)

HDMI Video/Audio Signal: Input Video Signal: 1.2 Volts p-p

Display Port Video/Audio Signal: Input Video Signal: 1.2 Volts p-p

VGA Video Signal: Input Video Signal: 1.2 Volts p-p

RJ45 Connectors: Shielded Link Connector, 2x HDBaseT, 1x LAN

Unit Control: TCP/IP on RJ45, Bi-directional RS-232, Serial IR, IR sensor, USB Micro

RS-232 Connector: 1x 3-pin terminal for unit control, 2x 3-pin terminal for pass-thru to/from HDBaseT Input and HDBaseT output

IR Connectors: 1x IR Sensor, 1x 2-pin terminal for unit control, 1x 3.5mm mono for IR input pass-thru to HDBaseT Output, 1x 3.5mm mono for IR output pass-thru from HDBaseT Output

RS-232 Connector: 3-pin phoenix terminal

General

Regulation: CE, RoHS, WEEE, EAC

Enclosure: Black metal

Product Dimensions: 8.27 x 6.42 x 1.75" (210 x 163 x 44.4mm)

Product Weight: Weight: 3.5 lbs / 1.59kg

Packaging Dimensions: 15.16 x 9.10 x 3.94 (385 x 230 x 100 mm)

Packaging Weight: 11.0 lbs / 5kg