

- **HDMI Bandwidth:** 600MHz/18Gbps
- **HDBaseT™ Bandwidth:** 340MHz/10.2Gbps
- **RX Input Port:** HDBaseT™ (RJ-45)
- **RX Output Port:** HDMI
- **RX Pass-through Ports:**
 - IR Extender (3.5mm)
 - IR Blaster (3.5mm)
 - RS-232 (DE-9)
- **TX Input Port:** HDMI
- **TX Output Port:** HDBaseT™ (RJ-45)
- **TX Pass-through Ports:**
 - IR Extender (3.5mm)
 - IR Blaster (3.5mm)
 - RS-232 (DE-9)
- **IR Frequency:** 30 - 50KHz (30 - 60KHz under ideal conditions)
- **Baud Rate:** Up to 115200
- **Power Supply:** 24V/1.25A DC (US/EU standards, CE/FCC/UL certified)
- **ESD Protection Human Body Model:**
 - ±8kV (Air Discharge)
 - ±4kV (Contact Discharge)
- **Dimensions (WxHxD):** 4 x 1 x 4.2 in (102x25x107.5mm) [Case Only] / 4 x 1 x 4.5 in (102x25x115mm) [All Inclusive]
- **Weight:** RX: 9.17 oz / 260g / TX: 8.61 oz / 244g
- **Chassis Material:** Metal (Steel)
- **Chassis Color:** Black
- **Operating Temperature:** 0°C-40°C/32°F-104°F
- **Storage Temperature:** -20°C-60°C/-4°F-140°F
- **Relative Humidity:** 20-90% RH (Non-condensing)
- **Power Consumption:** 14.5W (Tx+Rx)