

Hall Technologies KVM-HDU-4-X 4-Port HDMI KVM Switch with USB 2.0 Hub and 4K (UHD) Resolution Support (w/o accessories)

Video Standard:	HDMI
Number of Inputs:	4
Bandwidth:	300 MHz pixel clock or 10.2 Gbps video data rate
Max Resolution:	3840 x 2160 @ 60Hz (with 4:2:0 YUV color sampling) 3840 x 2160 @ 30Hz (with 4:4:4 YUV color sampling)
USB Standard:	Version 2.0
Connectors:	4x USB Type A Female for Hosts (PCs) 1x Keyboard Type A Female 1x Mouse Type A Female 2x USB 2.0 Peripherals from Built in Hub. Type A Female
Optional Power Supply:	2 VDC@ 2A Note: Power supply is not needed if USB inputs are connected
Power Consumption:	0.7 watts Excluding extra power drawn by USB devices that may be connected
Temperature / Humidity:	Storage: -40 to +158 °F (-40 to +70 °C) /10% to 90%, non-condensing Operating: +32 to +122 °F (0 to +50 °C) /10% to 90%, non-condensing
Cooling:	Convection
Enclosure type:	Metal
Dimensions:	9.65" x 3.74" x 1.61" (245mm x 95mm x 41mm)
Vibration:	ISTA 1A in carton (International Safe Transit Association)
Safety:	CE
EMI/EMC:	CE, FCC Class A
MTBF:	90,000 hours (Calculated Estimate)
Warranty:	3 years parts and labor