

PTZ

Protocol: More than 30 protocols such as Pelco-D/P, Samsung, Panasonic, Lilin, and Yaan

Video

Compression: H.264/H.265 decoding for IPC

Resolution: HD AVS: 2MP@25 fps/30 fps, 4MP@25 fps/30 fps, 5MP@20 fps, 6MP@20 fps, 4K@12.5 fps/15 fps
HD TVI: 2MP@25 fps/30 fps, 4MP@25 fps/30 fps, 5MP@20 fps
AHD: 2MP@25 fps/30 fps, 4MP@25 fps/30 fps
CVBS: NTSC, PAL
IP: 1MP, 1.3MP, 2MP, 3MP, 4MP, 5MP, 6MP, 8MP, 12MP

Network

Ethernet: 2 RJ45 10M/100M/1G

Protocol: ONVIF

Interface

RS485: 1

Audio I/O: 1 audio input
1 audio output

Electrical

Power Supply: Dedicated battery (replaceable), 7.4V polymer lithium ion batteries, up to 22.2Wh, working for about 8 hours

Environmental

Operating Conditions: -10°C to $+55^{\circ}\text{C}$ ($+14^{\circ}\text{F}$ to $+131^{\circ}\text{F}$)

Operating Humidity: 30%–95% (RH)

Construction

Gross Weight: 1.40 kg (3.09 lb)