

Camera

RAM/Rom: 64 MB, DDR2 RAM

Network

Ethernet: 1 x WAN port (can be configured to LAN) 10/100 Mbps, comply IEEE 802.3, IEEE 802.3u standards, supports auto MDI/MDIX

1 x LAN port, 10/100 Mbps, comply IEEE 802.3, IEEE 802.3u standards, supports auto MDI/MDIX

Protocol: TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, FTP, SMTP, SSL v3, TLS, ARP, VRRP, PPP, PPPoE, UPnP, SSH, DHCP, Telnet, SNMP, MQTT, Wake On Lan (WOL)

Wifi: 50 user support; WPA2-Enterprise (with external/ internal Radius server), WPA2-PSK, WPA-PSK, WEP, MAC Filter

Web Viewer: Multiple browser support; HTTP/HTTPS, status, configuration, FW update, CLI, troubleshoot, event log, system log, kernel log

Electrical

Power Supply: 9 – 30 VDC (4 pin industrial socket), reverse polarity protection, surge protection >33 VDC 10us max (Included)

Power Consumption: <5W

Enviromental

Operating Conditions: -40 °C to 75 °C

Ingress Protection: IP30

Construction

Casing: Aluminum housing, plastic panels

Dimensions: 83 mm x 74 mm x 25 mm (H x W x D)