

BZBGEAR BG-UDA-E14 1x4 4K UHD HDMI HDBaset Splitter/Distribution Amplifier over Category Cable (Kit, Includes 4x RX)

Technical	
HDMI Compliance	HDMI 2.0b
HDCP Compliance	HDCP 2.2/1.x
Video Bandwidth	594MHz/18Gbps
Video Resolution	Up to 4K2K @ 60Hz 4:4:4
Color Depth	8-bit, 10-bit, 12-bit (1080p @ 60Hz) 8-bit (4K2K @ 60Hz YUV4:4:4) 8-bit, 10-bit, 12-bit (4K2K @ 60Hz YCbCr 4:2:2/4:2:0)
Color Space	RGB 4:4:4, YCbCr 4:4:4 / 4:2:2 / 4:2:0
HDR	Support HDR, HDR10+, HLG, Dolby vision
HDMI Audio Formats	LPCM 2.0/2.1/5.1/6.1/7.1, Dolby Digital, Dolby TrueHD, Dolby Digital Plus(DD+), DTS-ES, DTS HD Master, DTS HD-HRA, DTS-X
Coaxial Audio Formats	PCM 2.0, Dolby Digital / Plus, DTS 2.0/5.1
Analog Audio Formats	PCM 2.0CH
ESD Protection	Human body model: ±8kV (Air-gap discharge) & ±4kV (Contact discharge)
Connection	
Input	1x HDMI Type A (19-pin female)
Output	1x HDMI Type A (19-pin female) 4x HDBaseT OUT [RJ45] 1x Coaxial Audio OUT [RCA] 1x L/R Audio OUT [5-pin phoenix connector]
Control	1x RS-232 (3-pin phoenix connector) 1x EDID DIP switch [5-pin] 1x IR IN [3.5mm Stereo Mini-jack] 1x IR OUT [3.5mm Stereo Mini-jack]
Mechanical	
Housing	Metal Enclosure
Silkscreen Color	Black
Dimensions	Transmitter: 8.7"(W) x 5.1"(D) x 1.6"(H) [220mm (W) x 130mm (D) x 40mm (H)] Receiver: 5.5"(W) x 2.6"(D) x 0.7"(H) [140mm (W) x 65mm (D) x 18mm (H)]
Weight	Transmitter: 1.9lbs [853g] Receiver: 0.54lbs [246g]
Power Supply	Input: AC100 - 240V 50/60Hz, Output: DC 24V/2.7A (US/EU standards, CE/FCC/UL certified)
Power Consumption	35W
Operation Temperature	32°F ~ 104°F / 0°C ~ 40°C
Storage Temperature	-4°F ~ 140°F / -20°C ~ 60°C
Relative Humidity	20~90% RH (non-condensing)