

PORTS

1 Female Connector (fixed cable end) for one of the following: VGA, HDMI, Audio, LAN, USB–2.0, USB–3.0, 3H2 or DisplayPort

1 Male Connector (retractor cable end) for one of the following: VGA, HDMI, Audio, LAN, USB–2.0, USB–3.0, 3H2 or DisplayPort

VIDEO

Max. Resolution (KRT-4-H, KRT-4-DP): 4K@60Hz (4:4:4)

KRT 4-3H2 EXTENDER ADDITIONAL SPECIFICATIONS

Optional External Power Source — 5V, 150mA micro USB port

Maximum Range for 4K@60Hz (4:4:4) Resolution — 10m from extender to display

Maximum Range for 4K@60Hz (4:2:0) / 4K@30 — 15m from extender to display

Maximum Range for 1080p@60Hz — 15m from extender to display

Maximum Resolution — 4K@60Hz (4:4:4)

Content Protection — Up to HDCP 2.2

ENVIRONMENTAL CONDITIONS

Operating Temperature: 0° to +40°C (32° to 104°F)

Storage Temperature: –40° to +70°C (–40° to 158°F)

Humidity: 10% to 90%, RHL non–condensing

REGULATORY COMPLIANCE (STANDARDS COMPLIANCE)

Safety: CE

Environmental: RoHs, WEEE

ENCLOSURE

Type: Plastic (ABS PC)

Color: Black

Fixed Cable Length: 20cm (7.9")

Retractable Cable Length: 180cm (71")

ACCESSORIES

Included: 4 M3x8 screws, WCP–(KRT) insert kit

PRODUCT WEIGHT

0.8kg (1.7lbs) approx.

SHIPPING DIMENSIONS

34.00cm x 26.00cm x 7.00cm (13.39" x 10.24" x 2.76") W, D, H

SHIPPING WEIGHT

1.0kg (2.2lbs) approx.
