

BZBGEAR BG-UC-MHD 1080P USB Conference Camera with Microphone

Camera Parameters	
Sensor	High quality HD CMOS sensor
Effective Pixels	16:9 2.07 megapixels
Video Format	1920×1080 @ 30fps/25fps; 1600×896 @ 30fps/25fps; 1280×720 @ 30fps/25fps; 1024×576 @ 30fps/25fps; 960×540 @ 30fps/25fps; 800×600 @ 30fps/25fps; 800×448 @ 30fps/25fps; 720×576 @ 30fps/25fps; 720×480 @ 30fps/25fps; 640×480 @ 30fps/25fps; 640×360 @ 30fps/25fps; 480×270 @ 30fps/25fps; 320×240 @ 30fps/25fps; 352×288 @ 30fps/25fps; 320×180 @ 30fps/25fps
View angle (default)	88° (D) / 80° (H) / 50°(V)
Focal length (default)	3.24mm
Focus	Fixed
Aperture	Fixed
Backlight contrast	On/OFF
Minimum illumination	0.5 Lux (F1.8, AGC ON)
Exposure	Exposure parameter could be adjusted; support auto exposure
Video Adjustment	Brightness, Color, Saturation, Contrast, White balance mode, Gain, Anti-flicker, Low brightness compensation etc.
SNR	>50dB
Input/Output Interface	
Video Interfaces	USB2.0 (power supply, upgrading available)
Video Compression Format	MJPEG, YUV, H.264, H.265
Audio Input Interface	Built in omnidirectional high sensitive digital pickup
Other Parameter	
Input Voltage	5V
Input Current	500mA (Max.)
Power consumption	2.5W
Store Temperature, Humidity	-10°C ~ +60°C, 20%~95%
Working Temperature, Humidity	-10°C ~ +50°C, 20%~80%
Dimension W×H×D	102mm*46mm*30mm
Weight (appx.)	0.15kg
Working Environment	Indoor Only