

Frequency response (-3 dB) ¹	51 Hz to 20 KHz
Frequency range (-10 dB) ¹	45 Hz to 20 KHz
Maximum SPL ²	123 dB

SPECIFICATIONS

Coverage (H x V)	120° x 40°
Amplifier rating	1000 W
LF channel rating	500 W
HF channel rating	500 W
Crossover frequency	200 Hz
Connectors	<ul style="list-style-type: none"> 4x XLR/TRS Combo Jack Line / Mic Input 1x 1/4" TRS HI-Z input 2x XLR/TRS Combo Jack for Stereo Line Input 1x Stereo RCA Input 1x 3.5 mm Stereo Input 1x Wireless Stereo Bluetooth® Audio Input 1x 1/4" Foot Switch Input 1x XLR MIX OUT Output 1x XLR AUX OUT Output
Enclosure	<ul style="list-style-type: none"> Sub: 15 mm plywood Column: Composite Pole: Aluminum Grille: Steel with black or white powder coat
Color:	Black or white
Dimensions (HxWxD): mm (in)	<ul style="list-style-type: none"> Sub: 448 x 332 x 432 (17.6 x 13.1 x 17) Column: 620 x 95 x 157 (24.4 x 3.7 x 6.2) Pole (2 pcs): 600 x 48 x 55 (23.6 x 1.9 x 2.2)
Net weight	<ul style="list-style-type: none"> Sub: 34.9 lb (15.8 kg) Column: 6.0 lb (2.7 kg) Pole (2 pcs): 3.1 lb (1.4 kg) Bag for column and pole: 1.9 (0.85 kg)
Shipping weight	53.4 lb (24.2 kg)
Power consumption ³	100-240 V AC, 50-60 Hz, 1.5-0.6 A

¹Half-space measurement using live DSP preset.

²Maximum SPL is measured at 1 m using broadband pink noise at maximum output.

³Current rating is 1/8 power.