

BZBGEAR BG-NDI-KIT-TOOL NDI Camera KIT for Live Streaming with Switcher and Controller

Sensor	1/2.8 inch high quality HD CMOS sensor
Effective Pixels	16: 9 2.07 megapixel
Video Format	HDMI/SDI: 1080P60 / 50 / 30 / 25 / 59.94 /29.97; 1080I60 / 50 / 59.94; 720P60 / 50 / 30 / 25 / 59.94 / 29.97
Minimum Illumination	0.5Lux (F1.8, AGC ON)
DNR	2D & 3D DNR
White Balance	Auto / Manual / One Push / 3000K / 4000K / 5000K / 6500K
Focus	Auto/Manual
Aperture	Auto/Manual
Electronic Shutter	Auto/Manual
BLC	ON/OFF
WDR	OFF/ Dynamic level adjustment
Video adjustment	Brightness, Color, Saturation, Contrast, Sharpness, B/W mode, Gamma curve
SNR	>55dB
Input/Output Interface	
Video Interfaces	NDI HX 4.0, SDI, HDMI, LAN(POE), RS232 (In & Out), RS485, A-IN
Image code stream	Double streams outputs simultaneously
Video Compression format	H.264, H.265
Control Signal Interface	RS-232 Ring through RS232 output, RS-485
Control Protocol	VISCA/Pelco-D/Pelco-P; Baud Rate: 115200/ 9600/ 4800/ 2400bps
Audio input Interface	Double track 3.5mm linear input
Audio Compression Format	AAC/MP3/PMC Audio compression
HD IP Interface	100M IP port (100BASE-TX); 5G WiFi (optional), support NDI & IP Visca control protocol
Network Protocol	NDI, RTSP/RTMP, ONVIF
Power Interface	HEC3800 outlet (DC12V)
PTZ Parameters	
Pan Rotation	±170°
Tilt Rotation	-30°~+90°
Pan Control Speed	0.1-180°/sec
Tilt Control Speed	0.1-80°/sec
Preset Speed	Pan: 60°/sec, Tilt: 30°/sec
Preset Number	255 presets (10 presets by remote controller)
Other Parameters	
Supply Adapter	AC110V-AC220V to DC12V/2A
Input Voltage	DC12V±10%
Input Current	1A (Max)
Consumption	12W (Max)
Store Temperature	-10°C to +60°C
Store Humidity	20% - 95%
Working Temperature	-10°C to +50°C
Working Humidity	20% - 80%
Dimension	150mm x 150mm x 167.5mm
Weight	1.4KG
Working Environment	Indoor Only

Remote Operation (IP)

Remote Upgrade, Reboot and Reset

BG-CJ-IPRSG2

Ethernet	One Ethernet port
Joystick	Four-dimensional (up, down, left, right) joystick control and clock, Zoom Tele/Wide
Control Protocol:	VISCA over IP
Display	LCD
Prompt Tone	Button Sound Prompts Open/Off
Power supply	DC 12V1A±10%
Power Consumption	0.6 W Max
Operating Temperature	0°C-50°C
Storage Temperature	-20°C-70°C
Dimensions(mm)	320x180x100