

## **BZBGEAR BG-UPTZ-KIT-TOOL Live Stream UPTZ Camera Kit with Joy Stick Controller and POE Switcher**

Image Sensor	1/2.8" Progressive CMOS
Effective Pixels	2.07 Megapixels (16:9)
Resolution	1080p60/50, 1080i60/50, 1080p30/25,720p60/50
Interface	USB 3.0, HDMI, 3G-SDI, LAN(POE), RS232/485, LINE IN
Pan Rotation	340°(max. speed: 80°/s)
Tilt Rotation	-30° to +90° (max. speed: 60°/s)
Focus System	Auto/Manual
S/N Ratio	≥50db
Preset Position	9 preset positions by IR remote controller, 255 preset positions by Keyboard or PC
Minimum Illumination	0.5 Lux (F1.8, AGC ON)
Exposure Control	Auto/Manual/Priority AE/Exposure Compensation/Bright
Shutter Speed	1/1~1/10,000s
Gain	Auto/Manual
White Balance	Auto/Manual/ATW/One-click/Indoor/Outdoor
Image Effect	Full color/black and white/Electronic flip
Video Output HD	HDMI, 3G-SDI, IP, USB 3.0
Control Protocol	RTSP, RTMP, ONVIF, GB/T28181
Power	12V DC
Power Consumption	Max. 30W(DC 12V)
Operating Temperature	32°F ~ 104°F / 0°C ~ +40°C
Storage Temperature	-4°F ~ 140°F / -20°C ~ +60°C
Camera Dimensions	(L)7 x (W)4.5 x (H)5.9in [(L)178 x (W)115.5 x (H)150.9mm]
Weight	3 lbs [1.38KG]
Color	Silver
Working Environment	Indoor Only

### **BG-CJ-IPRSG2**

<b>Ethernet</b>	One Ethernet port
<b>Joystick</b>	Four-dimensional (up, down, left, right) joystick control and clock, Zoom Tele/Wide
<b>Control Protocol:</b>	VISCA over IP
<b>Display</b>	LCD
<b>Prompt Tone</b>	Button Sound Prompts Open/Off
<b>Power supply</b>	DC 12V1A±10%
<b>Power Consumption</b>	0.6 W Max
<b>Operating Temperature</b>	0°C-50°C
<b>Storage Temperature</b>	-20°C-70°C
<b>Dimensions(mm)</b>	320x180x100