



dARTS™ THEATER

"THE DARTS SYSTEM IS SIMPLY THE BEST HOME THEATER
SOUND SYSTEM I HAVE HEARD SO FAR."

- Doug Blackburn

Widescreen
REVIEW & Custom Home
Theatre Design

"...IT'S UNCONDITIONALLY THE BEST LISTENING EXPERIENCE
I'VE EVER HAD IN A HOME THEATER."

- Darryl Wilkinson

**SOUND
& VISION**



Flyte Series

"I WAS COMPLETELY KNOCKED OUT BY THE SYSTEM."

- Bob Archer
CEPro

Featuring 5.25" woofers, this series is designed to provide a THX reference level of 105 dB SPL in rooms ranging from 2500 cubic feet to 8000 cubic feet.



DCB-Flyte



DIW-Flyte



DCB-112 SUB



DP4000 IA

Flyte 5.1 System

dARTS flyte were designed with aesthetics in mind, available in white or black, these small-form dARTS speakers are perfect for living rooms, media rooms, and the like. Price includes five (5) Flyte speakers in any configuration, one (1) DCB-112 Sub, and one (1) DP4000IA.

DCB-Flyte / DIW-Flyte

On-wall or In-wall speakers

Tweeter: 1.125" Soft Dome
Woofers: (2) 5.25" Glass Fiber/Nomex
Honeycomb/Glass Fiber
Dimensions:
DCB = 32"H x 6" W x 4" D
DIW = 32" H x 8" W x 3.9" D

DCB-112 SUB

Dual 12" subwoofer

Drivers: (1) 12.00" Active and (2) 12.00"
Passive Polypropylene with NBR Surround
Dimensions:
15.50" H x 14.50" W x 15.00" D

DP4000IA

Class D 16-Channel Digital Amplifier/ Controller
Crossover: DSP based, adaptive
Frequency Response within +/-0.5dB of
reference: 20 Hz - 20 kHz; ± 0.5 dB
Harmonic Distortion: 0.05% (@ 1 kHz)
Power Output: 125 w/ch @ 8Ω; 250 w/ch @ 4Ω
Inputs: 8 balanced (XLR), 16 unbalanced (RCA)
Power Requirements: 120/240V; 50/60 Hz
Programming Port: USB

The newest addition to the dARTS line-up, the Flyte system was designed to deliver the full dARTS sound and experience into any room or space desired, in attractive, thin enclosures.

Media rooms, family rooms, bedrooms, boardrooms, and offices - the Flyte system integrates into these spaces without disrupting the design or layout of the room in the process.

Flyte speakers are available in black or white, and as in-wall or on-wall variations.

Additional Flyte speakers, Atmos in-ceiling speakers, subwoofers and amps may be added to expand the system beyond the initial 5.1 configuration.

535 Series

Featuring 5.25" woofers, this series is designed to provide a THX reference level of 105 dB SPL in rooms ranging from 2500 cubic feet to 8000 cubic feet.



DCB-535-LR



DCB-535-LR



DCB-535-C



DP4000 IA

535 Custom Box

Custom-Built dARTS speakers are suitable for placement in cabinets or behind perforated projection screens. Their cabinets can be specially made for uniquely shaped mounting locations. Price includes two (2) DCB-535-LRs, one (1) DCB-535-C and one (1) DP4000IA.

DCB-535-LR

Main Speaker
 Tweeter: 1.125" Soft Dome
 Woofers: (2) 5.25" Glass Fiber/Nomex Honeycomb/Glass Fiber
 Dimensions: 12.00" H x 12.00" W x 7.50" D

DCB-535-C

Center Channel
 Tweeter: 1.125" Soft Dome
 Woofers: (2) 5.25" Glass Fiber/Nomex Honeycomb/Glass Fiber
 Dimensions: 7.00" H x 18.00" W x 9.25" D

DP4000 IA

Class D 16-Channel Digital Amplifier/ Controller
 Crossover: DSP based, adaptive
 Frequency Response within ± 0.5 dB of reference: 20 Hz - 20 kHz; ± 0.5 dB
 Harmonic Distortion: 0.05% (@ 1 kHz)
 Power Output: 125 w/ch @ 8 Ω ; 250 w/ch @ 4 Ω
 Inputs: 8 balanced (XLR), 16 unbalanced (RCA)
 Power Requirements: 120/240V; 50/60 Hz
 Programming Port: USB



DIW-535-LC



DIW-535-LC



DIW-535-LC



DP4000 IA

535 In-Wall

In-wall dARTS incorporate the same driver configuration as the Custom Box models, but mount flush with the wall for a seamless look. Price includes three (3) DIW-535-LCRs and one (1) DP4000IA.

DIW-535-LCR

Left, Center and Right Front Speakers
 Tweeter: 1.125" Soft Dome
 Woofers: (2) 5.25" Glass Fiber/Nomex Honeycomb/Glass Fiber
 Dimensions: 19.25" H x 14.25" W x 3.90" D
 Cutout Dimensions: 18.125" H x 13.25" W

DP4000 IA

Class D 16-Channel Digital Amplifier/ Controller
 Crossover: DSP based, adaptive
 Frequency Response within ± 0.5 dB of reference: 20 Hz - 20 kHz; ± 0.5 dB
 Harmonic Distortion: 0.05% (@ 1 kHz)
 Power Output: 125 w/ch @ 8 Ω ; 250 w/ch @ 4 Ω
 Inputs: 8 balanced (XLR), 16 unbalanced (RCA)
 Power Requirements: 120/240V; 50/60 Hz
 Programming Port: USB



DFS-535-LR



DFS-535-LR



DFS-535-C



DP4000 IA

535 Freestanding

Freestanding dARTS speakers are built into beautifully curved, high gloss cabinets in Gloss Black (BL) & Surround in Textured Satin. Price includes two (2) DFS-535-LRs, one (1) DFS-535-C and one (1) DP4000IA.

DFS-535-LR

Main Speaker
 Tweeter: 1.00" Soft Dome
 Woofers: 5.25" Glass Fiber/Nomex Honeycomb/Glass Fiber
 Dimensions: 11.50" H x 6.60" W x 6.90" D

DFS-535-C

Center Channel
 Tweeter: 1.00" Soft Dome
 Woofers: (2) 5.25" Glass Fiber/Nomex Honeycomb/Glass Fiber
 Dimensions: 6.60" H x 18.00" W x 9.60

DP4000 IA

Class D 16-Channel Digital Amplifier/ Controller
 Crossover: DSP based, adaptive
 Frequency Response within ± 0.5 dB of reference: 20 Hz - 20 kHz; ± 0.5 dB
 Harmonic Distortion: 0.05% (@ 1 kHz)
 Power Output: 125 w/ch @ 8 Ω ; 250 w/ch @ 4 Ω
 Inputs: 8 balanced (XLR), 16 unbalanced (RCA)
 Power Requirements: 120/240V; 50/60 Hz
 Programming Port: USB

535 Series

Featuring 5.25" woofers, this series is designed to provide a THX reference level of 105 dB SPL in rooms ranging from 2500 cubic feet to 8000 cubic feet.



Subwoofers

DCB-112 has one woofer and two bass radiators.

DCB-210 SUB

Drivers: (2) 10.00" Polypropylene with NBR Surround
Dimensions: 28.00" H x 14.00" W x 17.00" D

DCB-112 SUB

Drivers: (1) 12.00" Active and (2) 12.00" Passive Polypropylene with NBR Surround
Dimensions: 15.50" H x 14.50" W x 15.00" D



Subwoofers

DCB-115 and DIW210S have one woofer and one bass radiator.

DCB-115 SUB

Drivers: (1) 15.00" Active and (1) 15.00" Passive Polypropylene with NBR Surround
Dimensions: 19.50" H x 15.25" W x 22.40" D

DIW210S

Drivers: (1) 10.00" Active and (1) 10.00" Passive Mica-Graphite Polypropylene
Dimensions: 22.37" H x 13.00" W x 3.90" D



Surrounds

DCB-535-SURR (Custom Box)

Surround
Tweeters: (2) 1.00" Patented Woven Synthetic Soft Dome
Woofers: (2) 5.25" Glass Fiber/Nomex Honeycomb/Glass Fiber
Dimensions: 19.25" H x 10.50" W x 5.00" D

DIW-535-SURR (In-Wall)

Surround
Tweeters: (2) 1.00" Patented Woven Synthetic Soft Dome
Woofers: (2) 5.25" Glass Fiber/Nomex Honeycomb/Glass Fiber
Dimensions: 19.25" H x 14.25" W x 3.90" D



Atmos® In-Ceiling

DC-660-R

Surround
Tweeter: (2) 1.00" Variable Axis Soft Dome
Woofer: 6.50" Coax
Mounting Depth: 5.75"
Cutout Diameter: 8.375"

In-ceiling dARTS speakers allow greater placement flexibility in system installations and are perfect for Dolby Atmos® theater configurations. Includes magnetic Micro-Flange grille.

Additional DP4000 IA

DP4000 IA

Class D 16-Channel Digital Amplifier/ Controller
Crossover: DSP based, adaptive
Frequency Response within ± 0.5 dB of reference: 20 Hz - 20 kHz; ± 0.5 dB
Harmonic Distortion: 0.05% (@ 1 kHz)
Power Output: 125 w/ch @ 8 Ω ; 250 w/ch @ 4 Ω
Inputs: 8 balanced (XLR), 16 unbalanced (RCA)
Power Requirements: 120/240V; 50/60 Hz
Programming Port: USB

660 Series

Featuring 6.5" woofers, this series is designed to provide a THX reference level of 105 dB SPL in rooms ranging from 5000 to 18,000 cubic feet.



DCB-660-LR



DCB-660-LR



DCB-660-C



DP4000 IA

660 Custom Box

Custom-Built dARTS speakers are suitable for placement in cabinets or behind perforated projection screens. Their cabinets can be specially made for uniquely shaped mounting locations. Price includes two (2) DCB-660-LRs, one (1) DCB-660-C and one (1) DP4000IA.

DCB-660-LR

Main Speaker
 Tweeter: 1.125" Soft Dome
 Woofers: (2) 6.50" Glass Fiber/Nomex
 Honeycomb/Glass Fiber
 Dimensions: 14.00" H x 14.00" W x 9.00" D

DCB-660-C

Center Channel
 Tweeter: 1.125" Soft Dome
 Woofers: (2) 6.50" Glass Fiber/Nomex
 Honeycomb/Glass Fiber
 Dimensions: 8.25" H x 18.75" W x 12.00" D

DP4000 IA

Class D 16-Channel Digital Amplifier/ Controller
 Crossover: DSP based, adaptive
 Frequency Response within ± 0.5 dB of reference: 20 Hz - 20 kHz; ± 0.5 dB
 Harmonic Distortion: 0.05% (@ 1 kHz)
 Power Output: 125 w/ch @ 8 Ω ; 250 w/ch @ 4 Ω
 Inputs: 8 balanced (XLR), 16 unbalanced (RCA)
 Power Requirements: 120/240V; 50/60 Hz
 Programming Port: USB



DIW-660-LCR



DIW-660-LCR



DIW-660-LCR



DP4000 IA

660 In-Wall

In-wall dARTS incorporate the same driver configuration as the Custom Box models, but mount flush with the wall for a seamless look. Price includes three (3) DIW-660-LCRs and one (1) DP4000IA.

DIW-660-LCR

Left, Center and Right Front Speakers
 Tweeter: 1.125" Soft Dome
 Woofers: (2) 6.50" Glass Fiber/Nomex
 Honeycomb/Glass Fiber
 Dimensions: 23.50" H x 14.00" W x 3.50" D
 Cutout Dimensions: 22.375" H x 13.00" W

DP4000 IA

Class D 16-Channel Digital Amplifier/ Controller
 Crossover: DSP based, adaptive
 Frequency Response within ± 0.5 dB of reference: 20 Hz - 20 kHz; ± 0.5 dB
 Harmonic Distortion: 0.05% (@ 1 kHz)
 Power Output: 125 w/ch @ 8 Ω ; 250 w/ch @ 4 Ω
 Inputs: 8 balanced (XLR), 16 unbalanced (RCA)
 Power Requirements: 120/240V; 50/60 Hz
 Programming Port: USB



DFS-660-LR



DFS-660-LR



DFS-660-C



DP4000 IA

660 Freestanding

Freestanding dARTS speakers are built into beautifully curved, high gloss cabinets in Gloss Black (BL) & Surround in Textured Satin. Price includes two (2) DFS-660-LRs, one (1) DFS-660-C and one (1) DP4000IA.

DFS-660-LR

Main Speaker
 Tweeter: 1.00" Soft Dome
 Woofers: 6.50" Glass Fiber/Nomex
 Honeycomb/Glass Fiber
 Dimensions: 13.60" H x 7.90" W x 12.30" D

DFS-660-C

Center Channel
 Tweeter: 1.00" Soft Dome
 Woofers: (2) 6.50" Glass Fiber/Nomex
 Honeycomb/Glass Fiber
 Dimensions: 7.90" H x 22.00" W x 12.30" D

DP4000 IA

Class D 16-Channel Digital Amplifier/ Controller
 Crossover: DSP based, adaptive
 Frequency Response within ± 0.5 dB of reference: 20 Hz - 20 kHz; ± 0.5 dB
 Harmonic Distortion: 0.05% (@ 1 kHz)
 Power Output: 125 w/ch @ 8 Ω ; 250 w/ch @ 4 Ω
 Inputs: 8 balanced (XLR), 16 unbalanced (RCA)
 Power Requirements: 120/240V; 50/60 Hz
 Programming Port: USB

660 Series

Featuring 6.5" woofers, this series is designed to provide a THX reference level of 105 dB SPL in rooms ranging from 5000 to 18,000 cubic feet.



DFS-660-T



DFS-660-T



DFS-660-C



DP4000 IA

660 Tower

The newest addition to the dARTS family, the 660T is a powerful 3-way tower speaker. Price includes two (2) DFS-660-Ts, one (1) DFS-660-C and one (1) DP4000IA.

DFS-660-T

Main Speaker

Tweeter: 1.125" Soft Dome
Woofers: (3) 6.50" Glass Fiber/Nomex
Honeycomb/Glass Fiber
Dimensions: 45.50" H x 90.0" W x 14.70" D

DFS-660-C

Center Channel

Tweeter: 1.00" Soft Dome
Woofers: (2) 6.50" Glass Fiber/Nomex
Honeycomb/Glass Fiber
Dimensions: 7.90" H x 22.00" W x 12.30" D

DP4000 IA

Class D 16-Channel Digital Amplifier/ Controller
Crossover: DSP based, adaptive
Frequency Response within ± 0.5 dB of reference:
20 Hz - 20 kHz; ± 0.5 dB
Harmonic Distortion: 0.05% (@ 1 kHz)
Power Output: 125 w/ch @ 8 Ω ; 250 w/ch @ 4 Ω
Inputs: 8 balanced (XLR), 16 unbalanced (RCA)
Power Requirements: 120/240V; 50/60 Hz
Programming Port: USB



Subwoofers

DCB-112 has one woofer and two bass radiators.

DCB-210 SUB

Drivers: (2) 10.00" Polypropylene with NBR Surround
Dimensions: 28.00" H x 14.00" W x 17.00" D

DCB-112 SUB

Drivers: (1) 12.00" Active and (2) 12.00" Passive Polypropylene with NBR Surround
Dimensions: 15.50" H x 14.50" W x 15.00" D



Subwoofers

DCB-115 and DIW210S have one woofer and one bass radiator.

DCB-115 SUB

Drivers: (1) 15.00" Active and (1) 15.00" Passive Polypropylene with NBR Surround
Dimensions: 19.50" H x 15.25" W x 22.40" D

DIW210S

Drivers: (1) 10.00" Active and (1) 10.00" Passive Mica-Graphite Polypropylene
Dimensions: 22.37" H x 13.00" W x 3.90" D

660 Series

Featuring 6.5" woofers, this series is designed to provide a THX reference level of 105 dB SPL in rooms ranging from 5000 to 18,000 cubic feet.



Surrounds

DCB-660-SURR (Custom Box)

Surround

Tweeters: (2) 1.00" Patented Woven Synthetic Soft Dome

Woofers: (2) 5.25" Glass Fiber/Nomex Honeycomb/Glass Fiber

Dimensions: 19.25" H x 10.50" W x 5.00" D

DIW-660-SURR (In-Wall)

Surround

Tweeters: (2) 1.00" Patented Woven Synthetic Soft Dome

Woofers: (2) 5.25" Glass Fiber/Nomex Honeycomb/Glass Fiber

Dimensions: 19.25" H x 14.25" W x 3.90" D



Atmos® In-Ceiling

DC-660-R

Surround

Tweeter: (2) 1.00" Variable Axis Soft Dome

Woofers: 6.50" Coax

Mounting Depth: 5.75"

Cutout Diameter: 8.375"

In-ceiling dARTS speakers allow greater placement flexibility in system installations and are perfect for Dolby Atmos® theater configurations. Includes magnetic Micro-Flange grille.

Additional DP4000 IA

DP4000 IA

Class D 16-Channel Digital Amplifier/ Controller

Crossover: DSP based, adaptive

Frequency Response within $\pm 0.5\text{dB}$ of reference: 20 Hz - 20 kHz; $\pm 0.5\text{ dB}$

Harmonic Distortion: 0.05% (@ 1 kHz)

Power Output: 125 w/ch @ 8 Ω ; 250 w/ch @ 4 Ω

Inputs: 8 balanced (XLR), 16 unbalanced (RCA)

Power Requirements: 120/240V; 50/60 Hz

Programming Port: USB



NEW! Angled In-Ceiling

CI140D

Front Channel

Tweeter: 1.25" Soft Dome with Unicell Acoustic Treatment

Woofers: Two 5.25" Glass Fiber/Nomex Honeycomb/Glass Fiber

Mounting Depth: 6"

Cutout Diameter: 13.25 H x 13.4" W x 6" D

Custom Install CI140D dARTS speakers allow greater flexibility with front channel placement. Includes magnetic Micro-Flange grille.



a division of MSE Audio
www.dARTSdigitaltheater.com
www.mseaudio.com