

Specifications

Camera

Image Sensor: 1/2.8 2 Megapixel progressive scan STARVIS CMOS

Effective Pixels: 1920(H) x 1080(V)

RAM/Rom: 32MB/256MB

Scanning System: Progressive

Minimum Illumination: 0.002 Lux@F1.5

S/N Ratio: > 56 dB

IR Distance: Distance up to 150 m (492 ft)

IR On/Off Control: Auto/Manual

IR LEDs: 4

Lens

Lens Type: Motorized vari-focal

Mount Type: Board-in

Focal Length: 5.3-64mm

Max. Aperture: F1.5

Angle of View: H: 58°-4°, V: 34°-2°

Optical Zoom: 12x

Focus Control: Motorized

Close Focus Distance: 1.0 m-1.5 m (3.28 ft-4.92 ft)

DORI - Detect: 240ft-2897ft

DORI - Observe: 95ft -1158ft

DORI - 49ft-580ft
Recognize:

DORI - Identify: 23ft-289ft

Intelligence

IVS: Object Abandoned/Missing, Heat Map

Advanced Intelligent Functions: Perimeter Protection: Tripwire, Intrusion (Recognition of vehicle and people), fast moving, loitering detection, parking detection and people gathering.

Face Detection Support- Face detection; track; optimization; snapshot; report high quality picture; face enhancement; face exposure

Supports 6 kinds of face attributes extraction: Age, Gender, Expression (Happy, Surprised, Normal, Anger, Sad, Disgusted, Confused, Frightened), Glasses, Mouth, Mask, Mustache & Beard.

People Counting Support- Supports Line crossing/Region/Queuing people counting; Supports up to 4 rules.

Video

Compression: H.265,H.264,H.264B,H.264H, MJPEG (only supported by sub stream)

Streaming Capability: 3 Streams

Resolution: 1080P (1920 x 1080) / 1.3M (1280 x 960) / 720P (1280 x 720) / D1 (704 x 576 / 704 x 480) / VGA (640 x 480) / CIF (352 x 288 / 342 x 240)

Frame Rate: Main Stream: 1080P (1 fps–25/30 fps)
Sub Stream: D1 (1 fps–25/30 fps)
Third Stream: 1080P (1 fps–6 fps)

Bit Rate Control: CBR/VBR

Bit Rate: H.264: 32 Kbps–8192 Kbps
H.265: 19 Kbps–7424 Kbps

Day/Night: Auto(ICR) / Color / B/W

Backlight Compensation: BLC / HLC / WDR (120dB)

White Balance: Auto / Natural / Street Lamp / Outdoor / Manual

Gain Control: Auto / Manual

Noise Reduction: 3D DNR

Motion Detection: Off / On (4 Zone, Rectangle)

Region of Interest: Off / On (4 Zone)

Smart IR: Support

Flip: 0°/90°/180°/270°

Mirror: Off / On

Privacy Masking: Up to 4 areas

WDR: 120dB

Audio

Compression: G.711a, G.711Mu, AAC, G.726, G.723

Network

Ethernet: RJ-45 (100/1000Base-T)

Protocol: IPv4; IPv6;HTTP; HTTPS; TCP; UDP;ARP;RTP;RTSP;RTCP ;RTMP; SMTP;FTP;SFTP; DHCP; DNS; DDNS;QoS;UPnP ;NTP; Multicast; ICMP; IGMP;NFS;P PPoE; 802.1x; SNMP

Interoperability: ONVIF (Profile S/Profile G/Profile T), CGI

Compatibility: ONVIF Profile S&G / API

Streaming Method: Unicast / Multicast

Max. User Access: 20 Users

Edge Storage: NAS
Local PC for instant recording
Micro SD card 256GB

Web Viewer: IE, Chrome, Firefox, Safari

Management Software: SmartICRSS, DSS

Smart Phone: IOS, Android

Interface

Audio I/O: 1/1 channel In/Out

Memory Slot: Micro SD Card 256GB

Electrical

Power Supply: DC12V, PoE (802.3af)(Class 0)

Power Consumption: <10.3W

Environmental

Operating Conditions: -30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH

Storage Conditions: -30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH

Ingress Protection: IP67

Vandal Resistance: IK10

Construction

Casing: Metal

Dimensions: 273.2mm×95.0mm×95.0mm (10.76"×3.74"×3.74")

Gross Weight: 1.51Kg (3.33lb)

Mounting Pan/Tilt/Rotation: Pan:0°~360°; Tilt:0°~90°; Rotation:0°~360°