

E-Vision Laser 9000 WU

9,000 ISO / 8,000 ANSI Lumens | Contrast Ratio: 20,000:1 (dynamic) | Part No:120-481

E-VISION LASER 9000 WU DIGITAL PROJECTOR



THE VISIONARIES CHOICE

Colour System:

Laser Phosphor / 4 Segment (RGBY) Colourwheel / 2x120Hz

DMD Specification:

1920 x 1200 pixels native display.
Fast transit pixels for smooth greyscale and improved contrast.

Display Type:

1 x 0.67" DarkChip™ DMD™

Aspect Ratio:

16x10

Fill Factor

87%

Key Features

Video & Graphics Processing

- HDMI 2.0 for Side by Side, Frame Packing & Top Bottom 3D Formats.
- Dual Flash Processing can be used to multiply the displayed frame rate for 3D sources (example 144Hz display).
- Synchronisation of active glasses and compatible with polarised glasses
- 24p and 1080p native display.
- Sealed light engine
- DICOM Simulation Mode.
- HDR Support
- Powerful 7 point colour correction for accurate colour matching

Geometry Correction

- Cornerstone, Vertical & Horizontal Keystone.
- Selectable Aspect Ratios
- Digital Zoom

HDBaseT® Interface

- Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows projector to be placed up to 100m from source with low cost cabling.
- Projector Control via HDBaseT.

Source Compatibility:

HDMI including Deep Color™ processing.
Graphics standards support up to 3840 x 2160 (4K-UHD) & 4096 x 2160 (full 4K) resolution via HDMI
Graphics standards up to native 1920 x 1200 resolution @ 60Hz via DVI-D, HDBaseT or VGA
Component Video (SD and HD) via RGBHV.

Inputs/Outputs

Video & Computer			Communication & Control		
Type	Connector	Qty	Type	Connector	Qty
HDMI 2.0	HDMI	2	3D Sync Out	Mini DIN	1
DVI-D	DVI	1	3D Sync In	Mini DIN	1
VGA / Analog RGB	15-pin D-Sub	1	LAN	RJ45	1
Component Video	5 x BNC	5	Serial In (RS232)	9-pin D-Sub	1
HDBaseT	RJ45	1	Serial Out (RS232)	9-pin D-Sub	1
Video Out: VGA	15-pin D-Sub	1	Wired Remote In	3.5mm Stereo Jack	1
Audio In: Stereo	RCA	2	Wired Remote Out	3.5mm Stereo Jack	1
Audio In: Stereo	3.5mm Jack	1	12V Trigger	3.5mm Stereo Jack	1
Audio Out: Stereo	RCA	2	USB (power only)	USB Type A	1
			USB (Service)	USB Type B	1

3D Formats Supported	HDTV Formats Supported
Frame Packing Side By Side (half) Top and Bottom	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz), 1080i (50Hz, 60Hz), 720p (50, 60Hz)

Computer Compatibility	Bandwidth
Up to 1920 x 1200 via DVI-D, HDBaseT, VGA Up to 4096 x 2160 via HDMI	165 MHz on analog RGB 498 Megapixels per second on HDMI

Remote Control	Automation Control
IR remote control, wireless and wired. On-Board keypad	Crestron RoomView® Connected PLink - AMX SSDP LAN RS232 - AMX SSDP

Colour Temperature	Operation
User Selectable	24x7 Operation

Lamp Type	Typical Lamp Life
Laser Light Source	20,000 hours

Lenses			
Lens	Part No.	Optimised Focus	Lens Shift
0.77: 1 fixed	114-785	0.4m - 3.1m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame
0.77 - 1.1: 1 zoom (special order - call for info)	119-001	0.67m - 12.1m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame
1.1 - 1.3: 1 zoom	116-207	1m - 9m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame
1.25 - 1.6: 1 zoom (special order - call for info)	119-430	1.346m - 8.078m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame
1.54 - 1.93: 1 zoom	114-783	0.95m - 11.9m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame
1.93 - 2.91: 1 zoom	114-784	1.2m - 29.8m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame
3.0 - 5.0: 1 zoom	116-208	3m - 20m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame

* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/- 2%, INSIGHT Series: +/-2%,

Lens Mount
Manual shift, zoom & focus.

Mechanical Mounting	Orientation
Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes

Power Requirements	Power Consumption
100-240VAC 50/60Hz single phase	1000W

Thermal Dissipation	Fan Noise
3410 BTU/Hour	Typical 44dBA

Operating/Storage Temperature	Operating Humidity
Operating: 0 to 40C (32 to 104F) >35C switches to Eco Mode Storage: -20 to 60C (-4 to 140F)	10 to 85% non-condensing

Weight (Chassis Only)

25 kg
55.1 lb

Dimensions

L: 52.5 cm W: 47 cm H: 22.05 cm
L: 20.66 in W: 18.5 in H: 8.68 in

Safety & EMC Regulations

CE, FCC Class B, UL, CCC, CB, RoHS

Accessories

Accessory	Part No.
Infrared Remote (replacement)	117-880

**Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.*

Downloads

[PDF CAD Drawings](#)

[User Guides](#)

[AUTOCAD Drawings](#)

[User Guides German](#)

[User Guides French](#)

[Important Information](#)



Certificate Number 13629
ISO 9001

Specifications subject to change without notice. Digital Projection version: - ©2016 Digital Projection.
DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc

DIGITAL PROJECTION, LTD GREENSIDE WAY, MIDDLETON MANCHESTER, UK. M24 1XX
T: +44.161.947.3300 | F: +44.161.684.7674 | www.digitalprojection.co.uk

DIGITAL PROJECTION, INC 55 CHASTAIN ROAD, SUITE 115 KENNESAW, GA. 30144
T: 770.420.1350 | F: 770.420.1360 | www.digitalprojection.com

DIGITAL PROJECTION, CHINA Rm A2006, ShaoYaoJu 101 North lane, Shi AO International Center, Chao Yang District, Beijing, 100029, PR CHINA
T: +86.10.58239771 | F: +86 10 58239770

DIGITAL PROJECTION, ASIA 16 NEW INDUSTRIAL ROAD, #02-10 HUDSON TECHNOCENTRE SINGAPORE 536204
T: +65.6284.1138 | F: +65.6284.1238