

## PORTS

Encoder

**1 USB:** On a USB type B connector for host computer

**1 CAT 5/6:** On an RJ-45 connector

Decoder

**4 USB:** On USB type A connectors

**1 CAT 5/6:** On an RJ-45 connector

---

## EXTENSION LINE

**Direct Connect:** Up to 100m (330 ft) over solid core Cat 5e/6/7 cable

**Network Connect:** Up to 100m (330 ft) between switches over solid core CAT 5e/6/7 cable (One local to seven remote pairings supported for Simultaneous Users Interaction)

**Note:** For best performance use recommended Kramer cables

---

## GENERAL

**Maximum Throughputs:** USB 2.0 — Up to 480 Mbps\*

**Maximum Throughputs:** USB 1.1 — Up to 12 Mbps

**Traffic Types:** All USB 2.0 and 1.1 Traffic Types (Control, Interrupt, Isochronous and Bulk)

**Device Types:** All USB 2.0 and 1.1 Device Types and Classes

**Maximum Number of Connected USB Devices:** 30

**Networking Standards:** 1000BASE-T

**Networking Data Traffic:** Layer 2

**Networking Control Traffic:** Layer 3

---

## USER INTERFACE

**Controls:** Front panel pairing button

**Indicators:** Power, link, host, activity LEDs

---

## POWER

**Encoder Source:** Host computer

**Decoder Source:** 24V DC adapter

**Consumption:** 780mA

---

## ENCLOSURE

**Type:** Black anodized aluminum

**Cooling:** Convection ventilation

---

## ACCESSORIES

**Included:** 1 Power adapter, 1 USB2 type A male to type B male cable

---

## PRODUCT DIMENSIONS

18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00" ) W, D, H

---

**PRODUCT WEIGHT**

0.4kg (0.8lbs) approx.

---

**SHIPPING DIMENSIONS**

35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83" ) W, D, H

---

**SHIPPING WEIGHT**

1.2kg (2.6lbs) approx.

---