

BG-HDVS42U

4-Channel HDMI Live Streaming Audio/Video Mixer and Switcher (Available in gray/black)

The 4-channel BG-HDVS42U production switcher supports a host of features including live video switching, audio mixing, program and multiview outputs, PIP/POP, and custom logo overlay.

The full-featured HDMI video switcher is an ideal choice for production environments requiring HDMI switching like conferences, live events, and houses of worship.

Instant Control at Your Fingertips

- Upstream key: Luma key, Chroma key, PIP x2 / POP
- Downstream key and logo overlay

3

- FTB/MUTE/STILL/GPIO for tally customer configuration import and export
- Media library: 49 default patterns, 16 imported images, 16 captured images, 2 color generators
- AUX output configurable and assignable

Synergetic Technologies & Connections

- 4 channel auto-detected HDMI inputs
- 1x HDMI PGM output, 1x HDMI multiview out, 1x USB type-C output
- USB-C for capturing and streaming on PC
- Audio mixer: HDMI embedded audio and 2-Ch MIC/line In; audio delay available
- LAN port for PC software remote control

Quality Construction and Detail

- Solid, durable case ensures reliability for mobile production and permanently installed environments
- T-bar/Auto/Cut transitions; various effects: WIPE (9x2 patterns), MIX, DIP
- Control knob lets you access the control menu and adjust settings
- Enhanced buttons & LCD backlights







Specifications

| CONNECTION | |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video In | HDMI type-A x4 |
| Video Out | HDMI type-A PGM x1 HDMI type-A Multiview x1 USB2.0 type C x1 (Streaming on PC) Assignable HDMI 1~4, PGM, Clean PGM, PVW, Color bar, Multiview |
| Audio In | MIC/ Line level (3.5mm stereo audio) x2 |
| PC Control Port | LAN x1 |
| Media Library | USB type-A x1 (USB disk port for image import and firmware upgrade) |
| Tally Port | DB-15 x1 |
| Power In | DC 12V x1 |
| FUNCTIONS | |
| Transitions | T-Bar/ AUTO/ CUT |
| Effects | Wipe (9x2 patterns)/ Mix/ DIP/ Pattern/ Still (freeze)/ MUTE/ FTB |
| Layouts | 2 styles of Multiview layout (6 windows and status) |
| Keys | Upstream Key: Luma Key x1/ Chroma Key x1/ PiP x2/ POP Downstream Key: DSK x1/ Logo x1 |
| Audio Mixer | HDMI x4 and MIC/ Line level x2; Audio delay: 0-500ms |
| Media | Default image: 49 preset patterns Local image: up to 16 imported images Capture image: up to 16 captured images |
| Generators | Pattern generator xl Color generators x2 |
| STANDARDS | |
| HDMI In Format Support | 1080p 60/ 59.94/ 50/ 30/ 29.97/ 25/ 24/ 23.98 1080i 50/ 59.94/ 60 720p 60/ 59.94 /50/ 30/ 29.97/ 25/ 24/ 23.98 576i 50, 576p 50, 480p 59.94/ 60, 480i 59.94/ 60 |
| HDMI PGM Out | 1080p 60/ 59.94/ 50/ 48/ 47.95/ 30/ 29.97/ 25/ 24/ 23.98; 1080i 60/ 59.94/ 50 |
| HDMI Multiview Out | 1080p 60/ 59.94/ 50/ 48/ 47.95/ 30/ 29.97/ 25/ 24/ 23.98; 1080i 60/ 59.94/ 50 |
| HDMI Color Space | RGB/ YUV |
| USB Capture Out | MJPG, Up to 1080p 60 |
| Media Format | USB disk format support: FAT32, Ext3, Ext4, up to 256GB Image format support: png, bmp, jpg, gif, jpeg, ppm, pbm, tif, jps, mpo, tga Logo format support: png, bmp, jpg, gif, jpeg, ppm, pbm, tif, jps, mpo, tga Logo size support: 10×10 pixel to 600×600 pixel |
| OTHERS | |
| Power | Wide voltage: 7~24V; Operating power: 12W (12V 1A) |
| Dimension (L×W×D) | 245 x 143 x 45 mm |
| Weight | Net: 2.3 lbs; Gross: 3.3 lbs |
| Temperature | Working: -20°C~60°C, Storage: -30°C~70°C |

Industry-Leading Warranty & Support

BZBGEAR Pro AV products and Cameras come with a three-year warranty. An extended two-year warranty is available for our Cameras upon registration for a total of five years.



We pride ourselves in our Customer Service and seven-days-a-week Tech Support.



830 National Drive, Suite 140 Sacramento, CA 95834

1.888.499.9906 info@bzbgear.com