

INPUTS

2 HDMI: On female HDMI connectors

OUTPUTS

1 HDMI: On a female HDMI connector

PORTS

1 Ethernet: On an R–J45 connector

1 Balanced Audio: On a 5–pin terminal block connector

Serial USB: On a mini USB connector

VIDEO

Compression Standard: H.264 or H.265

Max Resolution – One Stream: 4K@60Hz (4:4:4)

Max Resolution – Two Simultaneous Streams: 4K@60Hz (4:2:0)

USER INTERFACE

Indicators: Link and power LEDs

Controls: Restart and factory reset front panel buttons, API, embedded web pages, and RTSP via Ethernet, API commands via serial USB

POWER

Source: 12V DC

Consumption: 20.4W

ENVIRONMENTAL CONDITIONS

Operating Temperature: 0 to + 45°C (32 to + 113 °F), 10% to 90%, non–condensing

Storage Temperature: –20 to +70°C (–4 to + 158 °F), 10% to 90%, non–condensing

Humidity: 10% to 90%, non–condensing

PRODUCT DIMENSIONS

14.30cm x 12.20cm x 4.36cm (5.63" x 4.80" x 1.72") W, D, H

PRODUCT WEIGHT

0.5kg (1.1lbs) approx.

SHIPPING DIMENSIONS

31.90cm x 16.50cm x 6.70cm (12.56" x 6.50" x 2.64") W, D, H

SHIPPING WEIGHT

1.0kg (2.3lbs) approx.

