



KRAMER

KRT-4

Cable Retractor



KRT-4 is a cable retractor designed for installing in a meeting room, classroom or other AV site. KRT-4 extends a variety of common AV connector types and is easy to install and use

FEATURES

Provides Convenient and Easy-to-Use Connecting - Pull the cable to extend up to 1.8m (5.9ft) from the installation site; the cable automatically locks in position to the desired length. When finished, pull the cable again and it retracts into the housing

Improved Design - Gentle retraction feature extends the life of the cable and connector

Simple and Flexible Installation Options - Install in compatible Kramer TBUS models or attach directly to the underside of a table with a few screws

Available in Most Common AV Connector Types - HDMI, VGA, audio (3.5mm), LAN, USB, USB-C, and DisplayPort



TECHNICAL SPECIFICATIONS

| | |
|--|--|
| Ports | 1 Female Connector (fixed cable end) for one of the following: VGA, HDMI, Audio, LAN, USB-2.0, USB-3.0, USB-C, 3H2 or DisplayPort 1 Male Connector (retractor cable end) for one of the following: VGA, HDMI, Audio, LAN, USB-2.0, USB-3.0, USB-C, 3H2 or DisplayPort |
| Video | Max. Resolution (KRT-4-H, KRT-4-DP) 4K@60Hz (4:4:4) |
| KRT 4-3H2 Extender Additional Specifications | Optional External Power Source – 5V, 150mA micro USB port Maximum Range for 4K@60Hz (4:4:4) Resolution – 10m from extender to display Maximum Range for 4K@60Hz (4:2:0) / 4K@30 – 15m from extender to display Maximum Range for 1080p@60Hz – 15m from extender to display Maximum Resolution – 4K@60Hz (4:4:4) Content Protection – Up to HDCP 2.2 |
| KRT-USBC Additional Specifications | Max. Data Rate: 10Gbps Power Rating: 3A max Max. Resolution: 4K 30Hz |
| Environmental Conditions | Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -40° to +70°C (-40° to 158°F) Humidity: 10% to 90%, RHL non-condensing |
| Regulatory Compliance (Standards Compliance) | Safety CE Environmental RoHs, WEEE |
| Enclosure | Type: Plastic (ABS PC) Color: Black Fixed Cable Length: 20cm (7.9") Retractable Cable Length: 180cm (71") |
| Accessories | Included: 4 M3x8 screws, WCP-(KRT) insert kit |
| Product Dimensions | 20.40cm x 0.00cm x 3.63cm (8.03" x 0.00" x 1.43") W, D, H |
| Product Weight | 0.8kg (1.7lbs) approx |
| Shipping Dimensions | 34.00cm x 26.00cm x 7.00cm (13.39" x 10.24" x 2.76") W, D, H |
| Shipping Weight | 1.0kg (2.2lbs) approx |



KRAMER

CONFIGURATIONS

| | |
|-------------|---|
| KRT-4-H | High-speed HDMI with Ethernet cable retractor with HDMI connector |
| KRT-4-DP | DisplayPort cable retractor with DisplayPort connector |
| KRT-4-VGA | VGA cable retractor with VGA connector |
| KRT-4-LAN | CAT 6 cable retractor with RJ-45 connector |
| KRT-4-A | Audio cable retractor with 3.5mm mini jack connector |
| KRT-4-USB-3 | USB 3.0 cable retractor with USB type-A connector |
| KRT-4-3H2 | High-Speed HDMI 4K cable retractor with PT-3H2 signal extender |
| KRT-4-USBC | USB type-C cable retractor for data, video, and charging |