

Hollyland HL-Mars 400S PRO-RX Mars 400S PRO SDI/HDMI Wireless Video Receiver

Wireless Range with Transmitter	400' (121.92m) (Line-of-Sight)
Channel Bandwidth	20 MHz
Frequency Range	5 GHz
Latency	< 0.08 sec
RF Sensitivity	-80 dBm
Wi-Fi	Yes
Wireless	
Antenna Ports	2x RP-SMA Male
Video Connectors	1x BNC (3G-SDI) Output 1x HDMI Output
Other I/O	1x USB Type-C 1x DC Input
Embedded Audio	SDI HDMI
Interface	
Video Format	SDI/BNC: 1080p at 23.98, 24, 25, 29.97, 30, 50, 59.94, 60 fps 1080i at 50, 59.94, 60 fps 1080PsF at 23.98, 24, 25 fps 720p at 50, 59.94, 60 fps HDMI: 1080p at 23.98, 24, 25, 29.97, 30, 50, 59.94, 60 fps 1080i at 50, 59.94, 60 fps 720p at 50, 59.94, 60 fps 576p at 50 fps 480p at 60 fps
Format Support	
Panel Type	OLED
Display	
Battery Support	1x Sony L-Series / NP-F Type
Power Connector	1x Barrel (6 to 16V DC) Input
Power Consumption	Device: (7 W)
Power	
Mounting	1x 1/4"-20 Female 1x Integrated Cold Shoe
Materials	Metal
Battery Info	Required, not included
Battery Material	Lithium
Battery Quantity	1
Battery Type	Sony L-Series / NP-F Type
Dimensions	4.33 x 2.83 x 1.34" (11.0 x 7.2 x 3.4cm)
Weight	0.5 lbs (206g)