

Panel	Panel Type:	LED-Backlit TFT LCD (IPS Technology)
	Panel Size:	85.6"
	Max. Resolution:	UHD 3840 x 2160
	Pixel Pitch:	0.494 mm
	Brightness:	350 cd/m ²
	Contrast Ratio:	1200:1
	Viewing Angle (H/V):	178°/178°
	Display Colour:	1.07B
	Response Time:	5 ms
	Surface Treatment:	Anti-Glare treatment (Haze 28%), 2H Hard coating
Frequency	Frequency (H):	30 kHz-80 kHz
	Frequency (V):	50 Hz-76 Hz
Signal Input	HDMI:	2.0 x 3
	VGA:	15-Pin D-Sub x 1
Signal Output	HDMI:	2.0 x 1
External Control	RS232 In:	9-Pin D-Sub
	LAN:	RJ45 x 1
Embedded Player	OS:	Android 8.0
	CPU:	Dual core A73+Dual core A53
	Memory:	3 GB
	Storage:	16 GB
Other Connectivity	USB:	2.0 x 3 / 3.0 x 3
Audio	Audio In:	Stereo Audio Jack (3.5 mm)
	Audio Out:	Stereo Audio Jack (3.5 mm), S/PDIF
	Internal Speakers:	16W x 2
Touch Screen	Technology:	Infrared Touch Frame
	Positional Accuracy:	±1.5 mm
	Panel Interface:	USB 2.0 x 2 (Type-B)
	Single Touch Plug & Play:	Windows 2000/XP/Vista/CE 6.0, macOS
	Multi-touch Plug & Play:	Windows 7/8/10, Android/Linux (kernel version 3.5+), Chrome OS (39 or above)
	Multi-touch Support by Driver:	macOS (supported by UPDD driver)
Power	Power Requirements:	AC 100-240V, 50/60 Hz
	On Mode:	294W
	Standby Mode:	< 0.5W
	Off Mode:	< 0.3W

Glass	Thickness:	4.0 mm (0.16")
	Reflection Rate:	< 10%
	Transmission Rate:	≥ 88%
	Hardness:	≥ 8H
	COM_FIELDS_GLOSS:	75±5 GU
Operating Conditions	Temperature:	0°C-40°C (32°F-104°F)
	Humidity:	10%-90% (non-condensing)
Mounting	VESA FPMPMI:	Yes (800 x 600 mm)
Dimensions	Product w/o Base (W x H x D):	1957.2 x 1160.0 x 86.0 mm (77.1" x 45.6" x 3.4")
	Packaging (W x H x D):	2211.0 x 1370.0 x 280.0 mm (87.1" x 53.9" x 11.0")
Weight	Product w/o Base:	66.0kg (145.5 lb)
	Packaging:	98.8kg (217.8 lb)
Regulation Approval	Certifications & Compliance:	CE, LVD, FCC, WEEE, REACH, RoHS
Accessories	Supplied:	Power Cord, HDMI Cable, USB Cable, Remote Control, Batteries, Quick Start Guide, Touch Pen, Wall Mount, Wi-Fi / Bluetooth Module
Optional Accessories	Floor Mount (Landscape only):	FMC-03+LMK-04, FMC-04+LMK-04
Power	Power Supply:	Internal
Storage Conditions	Temperature:	-20°C-60°C (-4°F-140°F)
	Humidity:	10%-90%(non-condensing)