

A-NeuVideo ANI-0104POE-XT 1x4 HDMI POE 1080/4K30 CAT6 Extender Splitter/IR Return with 4x Receivers 230ft/70m Auto Setup

- **HDMI Compliance:** HDMI 1.4
- **HDCP Compliance:** HDCP 1.4
- **Video Bandwidth:** 297MHz/10.2Gbps
- **Video Resolution:** 480i ~1080p50/60Hz, 4K30Hz (4:4:4)
- **Color Depth:** 8-bit,10-bit,12-bit (1080p@60Hz); 8-bit (4K30Hz)
- **Color Space:** RGB, YCbCr_4:4:4/4:2:2. YUV_4:2:0
- **Audio Formats:** LPCM 7.1CH, Dolby True HD, and DTS-HD Master Audio
- **ESD Protection Human Body Model:**
 - ±8kV (Air Discharge)
 - ±4kV (Contact Discharge)
- **Transmitter:**
 - **Input:** HDMI IN [Type A, 19-pin female]
 - **Outputs:**
 - HDMI OUT [Type A, 19-pin female]
 - (4) CAT OUT [RJ45] with Indicators
 - **Controls:**
 - IR OUT [3.5mm Stereo Mini-jack]
 - EDID DIP switch [4-pin]
 - Update [Micro USB]
- **Receiver:**
 - **Inputs:**
 - IR IN [3.5mm Stereo Mini-jack]
 - CAT IN [RJ45, 8-pin female]
 - **Output:** HDMI OUT [Type A, 19-pin female]
- **Power Supply:** 12V/1A DC Locking Power (US/EU standards, CE/FCC/RoHS certificated)
- **Dimensions (WxHxD):** Transmitter: 8.3 x 3.3 x .7 in (210x83x18mm) / Receiver: 3.1 x 2.7 x .65 in (79.5x69x16.5mm)
- **Weight:** Transmitter: 15.8 oz/448g / Receiver: 4.6 oz/130g
- **Housing:** Metal Enclosure
- **Color:** Grey
- **Operating Temperature:** 0°C-40°C/32°F-104°F
- **Storage Temperature:** -20°C-60°C/-4°F-140°F
- **Relative Humidity:** 20-90% RH (Non-condensing)
- **Power Consumption:** 11W