

AUDIO & Video

Video Resolutions (Max)	Video Resolutions 1920x1080p @60Hz 16bit 3840x2160 @30Hz 8bit 4:4:4 3840x2160 @60Hz 8bit 4:2:0
	Note: to send video from a computer an additional cable is required depending on the source device's output capability, such as an HDMI to USB 3.0 adapter or a USB-C to USB Type A cable

Supported Standards	DCI RGB HDR10+ USB
----------------------------	--------------------------

Maximum Pixel Clock	300Mhz
----------------------------	--------

Communication and Control

USB	USB3.2(Gen 2), USB3.1(Gen 2), USB3.1(Gen 1), USB 2.0 Max bandwidth: 10Gbps
------------	---

Power

Power Supply	≤0.2W(Both sides)
---------------------	-------------------

Power Carry	Max: 5v 900mA
--------------------	---------------

Environmental

Operating Temperature	0 ~ +75°C (32 ~ +167 °F), 10% ~ 85%, non-condensing
------------------------------	---

Storage Temperature	-20 ~ +70°C (-4 ~ +158 °F), 10% ~ 85%, non-condensing
----------------------------	---

Installation	Cable bend radius: 9mm Fiber Pulling/Tensile Strength: 10kg (100n)
---------------------	---

Dimensions & Weight

Length x Width x Height	Type A Male Connector: 40mm x 18mm x 5mm Type A Female Connector: 38mm x 18mm x 5mm
--------------------------------	--

Cable Diameter	4.5mm
-----------------------	-------

Regulatory

Safety and Emission	CE FCC RoHS RCM EAC FT6 Plenum CPR
----------------------------	--
