

# Kramer WP-2UT/R-KIT-D(W) USB 2.0 PoC Wall-Plate Extender Kit over Extended-Reach CAT

## INPUTS

- 1 CAT: On an RJ-45 female connector for extension line (PT-2UR)

## OUTPUTS

- 1 CAT: On an RJ-45 female connector for extension line (WP-2UT)

## PORTS

- 1 USB: On a USB-B female connector for USB host extension (WP-2UT)
- 4 USB: On USB-A female connectors for USB devices extension (PT-2UR)
- 1 RS-232: On a 3-pin terminal block connector for serial link extension

## EXTENDED USB

- Data Rate: Up to 480Mbps
- Transmitted Data Bandwidth: Up to 300Mbps
- Standards Compliance: USB 1.1 and 2.0

## EXTENSION LINE

- Reach Using Shielded UNIKAT Cables: Up to 100m (330ft)
- Reach Using CAT 5e Cables: Up to 30m (100ft)
- Baud Rate: 9600

## PT-2UR USB CHARGING

- Max Total Current When PSU-Powered: 2.5A
- Max Current Per Port When PSU-Powered: 2A
- Max Total/Per-port Current When PoC-Powered: 0.5A

## USER INTERFACE

- Indicators: LINK and ON LEDs

## POWER

- Source: 12V DC, 2A
- WP-2UT Consumption: 1.1A
- PT-2UR Consumption: 1.85A

## ENCLOSURE

- Transmitter Size: 1-gang US
- Receiver Size: PicoTools®
- Type: Aluminum
- Cooling: Convection ventilation

## ACCESSORIES

- Included: 1 12V power-supply, 1 C-USB/AB-6 USB type-A male to USB type-B male 2m cable, US 1-gang, white wall-plate frame and faceplate, 1 bracket set

## STANDARDS COMPLIANCE

- CE, FCC

## PRODUCT DIMENSIONS

- 6.98cm x 3.10cm x 11.43cm (2.75" x 1.22" x 4.50" ) W, D, H

## PRODUCT WEIGHT

- 0.3kg (0.7lbs) approx.

## SHIPPING DIMENSIONS

- 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94" ) W, D, H

## SHIPPING WEIGHT

- 0.6kg (1.3lbs) approx.