

Specifications	RX-22G	RX-24G
Panel		
Panel Type	LED-Backlit TFT LCD (TN Technology)	LED-Backlit TFT LCD (VA Technology)
Panel Size	21.5"	23.8"
Max. Resolution	FHD 1920 x 1080	FHD 1920 x 1080
Pixel Pitch	0.248 mm	0.274 mm
Brightness	250 cd/m ²	250 cd/m ²
Contrast Ratio	20,000,000:1 (DCR)	20,000,000:1 (DCR)
Viewing Angle (H/V)	170°/160°	178°/178°
Display Colour	16.7M	16.7M
Response Time	3 ms	5 ms
Surface Treatment	-	Seriesant1-Glare Treatment (Haze 40%),3H Hard Coating
Frequency		
Frequency (H)	24 kHz-83 kHz	24 kHz-83 kHz
Frequency (V)	50 Hz-75 Hz	50 Hz-75 Hz
Signal Input		
DisplayPort	x 1	x 1
HDMI	1.4 x 1	1.4 x 1
DVI	24-Pin DVI-D	24-Pin DVI-D
VGA	15-Pin D-Sub x 1	15-Pin D-Sub x 1
Composite	BNC x 2	BNC x 2
S-Video	4-Pin mini DIN x 1	4-Pin mini DIN x 1
Signal Output		
Composite	BNC x 2	BNC x 2
External Control		
RS232 In	2.5 mm Phone Jack	2.5 mm Phone Jack
Other Connectivity		
USB	2.0 x 1 (Service Port)	2.0 x 1 (Service Port)
Audio		
Audio In	Stereo Audio Jack (3.5 mm), Stereo Audio Jack (RCA)	Stereo Audio Jack (3.5 mm), Stereo Audio Jack (RCA)
Audio Out	Stereo Audio Jack (RCA)	Stereo Audio Jack (RCA)
Internal Speakers	2W x 2	2W x 2
Power		
Power Requirements	DC 12V, 2.1A	DC 12V, 2.75A
On Mode	18W (On)	20W (On)
Standby Mode	< 0.5W	< 0.5W
Off Mode	< 0.3W	< 0.3W
Power Supply	External	External
Glass		
Thickness	3.0 mm (0.12")	3.0 mm (0.12")
Reflection Rate	< 1%	< 1%
Transmission Rate	> 97%	> 97%
Hardness	> 9H	> 9H
Operating Conditions		
Temperature	0°C-40°C (32°F-104°F)	0°C-40°C (32°F-104°F)
Humidity	10%-90% (non-condensing)	10%-90% (non-condensing)
Storage Conditions		
Temperature	-20°C-60°C (-4°F-140°F)	-20°C-60°C (-4°F-140°F)
Humidity	5%-95% (non-condensing)	5%-95% (non-condensing)
Mounting		
VESA FPMPMI	Yes (100 x 100 mm & 75 x 75 mm)	Yes (100 x 100 mm & 75 x 75 mm)
Stand		
Tilt	0° to 17°	3° to 21°
Security		
Kensington Security Slot	Yes	Yes
Dimensions		
Product with Base (W x H x D)	513.2 x 368.5 x 155.0 mm (20.2" x 14.5" x 6.1")	562.4 x 392.8 x 196.0 mm (22.1" x 15.4" x 7.7")
Product w/o Base (W x H x D)	513.2 x 324.3 x 56.2 mm (20.2" x 12.8" x 2.2")	562.4 x 352.6 x 56.2 mm (22.1" x 13.9" x 2.2")
Packaging (W x H x D)	614.0 x 477.0 x 204.0 mm (24.2" x 18.8" x 8.0")	672.0 x 517.0 x 249.0 mm (26.5" x 20.4" x 9.8")
Weight		
Product w/o Base	6.0 kg(13.2 lb)	7.3 kg (16.1lb)
Product with Base	6.7 kg(14.8 lb)	8.1 kg (17.9lb)
Packaging	8.8 kg(19.4 lb)	11.2 kg (24.7lb)
Regulation Approval		
Certifications & Compliance	BSMI, CB, CE, FCC, CCC, RoHS, WEEE, REACH	CE, LVD, WEEE, RoHS, REACH, EAC, BSMI, FCC
Accessories		
Supplied	Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card	Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card
Optional Accessories		
Ceiling Mount (Landscape only)	CMP-01+WMK-03	CMP-01+WMK-03
Wall Mount (Landscape only)	WMA-01, WMK-01, WMK-03, PMK-01	WMA-01, WMK-01, WMK-03, PMK-01
Desk mount (Landscape only)	DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02	DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02