

<b>NVD-30 MARK II IP Video Decoder-HDMI</b>	
Audio/Video Input	Stream Input <ul style="list-style-type: none"> <li>· RTSP over UDP (Unicast / Multicast)</li> <li>· RTSP over TCP</li> <li>· RTSP over HTTP</li> <li>· SRT (Secure Reliable Transport) caller</li> <li>· MPEG-TS over UDP</li> <li>· RTMP Pull</li> <li>· RTMP Push (Internal Server)</li> <li>· UDP raw (Unicast/Multicast)</li> <li>· HLS over HTTP</li> <li>· MPEG-TS over TCP Pull</li> <li>· Video sharing websites</li> </ul>
Audio Output	2 x RCA(L/R) HDMI embedded audio
Video Output	Composite (analogue) HDMI (digital)
Network Feature	1x RJ-45 Female (10/100M Ethernet) DHCP/Static IP
Supported Video Resolution	1080p 60/59.94/30/29.97/25/24 1080i 60/59.94/50 720p 60/59.94/50 576i 50 (PAL) 480i 60 (NTSC)
Supported Decoding Resolution	Up to 1080p60/50
Control	Web browser UI for configuration and control. TCP/IP Socket commands
Update	Automatic firmware upgrade
Power	DC 12V, 0.5A
Environmental Conditions	Operating temperature: 0~40°C, Storage temperature: -10~60°C
Dimension (LxWxH)	220 x 143 x 47 mm
Weight	1 kg