

Size	31.5"
Resolution	1920 x 1080 (16:9)
Pixel Pitch	0.121(H) × 0.363(W) mm
Color Depth	16.7M
Viewing Angle (Typ.)	178°(H) / 178°(V)
Luminance (Max.)	400 cd/m ²
Contrast Ratio	1200:1
Display Area	698.4(H) × 392.85(V) mm

Input

2 x BNC	SDI Input
1 x DVI - D	DVI Input
2 x SFP	In/Out (combined)
1 x HDMI	HDMI Input

Output

2 x BNC	SDI Output
---------	------------

Input Signal

3G-SDI	2.970Gb/s
HD-SDI	1.485Gb/s
SD-SDI	270Mb/s
DVI	VESA/IBM Modes
HDMI	1080p(60/59.94/50/30/25/24/23.98)/ 1080i(60/59.94/50)/720p(60/50)/ 480i(60)/480p(60)/576i(50)/576p(50)

SDI Input Signal Formats

SMPTE-2048	2048×1080p(24/24sF/23.98/23.98sF)
SMPTE-425M-A/B	1080p(60/59.94/50/30/29.97/25/24/23.98/ 30sF/29.97sF/25sF/24sF/23.98sF)
SMPTE-274M	1080i(60/59.94/50)
	1080p(30/29.97/25/24/24sF/23.98/23.8sF)
SMPTE-296M	720p(60/59.94/50)
SMPTE-125M	480i(59.94)
ITU-R BT.656	576i(50)
Audio IN	Embedded Audio Analog stereo (Phone Jack)
Power	AC 100 ~240V (50~60Hz)
Power Consumption (Approx.)	TBD
Operating Temperature	0°C to 45°C (32°F to 113°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Basic Accessory	AC Power Cord / Remote Control / USB Cover / Stand