

Column array	8x 3.5" neodymium drivers
Subwoofer	1x 12"
Frequency response (-3 dB)	43 Hz - 20 KHz
Frequency range (-10 dB)	37 Hz - 20 KHz

SPECIFICATIONS

Maximum SPL	127 dB
Coverage (H x V)	120° x 40°
Amplifier rating	1000 W
LF channel rating	500 W
HF channel rating	500 W
Crossover frequency	200 Hz
Connectors	<ul style="list-style-type: none"> 4x XLR/TRS combo jack line/mic input 2x XLR/TRS combo jack for stereo line input 1x 1/4" TRS Hi-Z input 1x stereo RCA input 1x 3.5 mm stereo input 1x wireless stereo Bluetooth® audio input 1x 1/4" foot switch input 1x XLR mix out output 1x XLR aux out output 1x RJ45 QuickSmart Link connector
Enclosure	<ul style="list-style-type: none"> Column: composite Pole: aluminum Sub: 15 mm plywood
Grille	Steel with black or white powder coat
Colors	Black or white
Dimensions (HxWxD): in (mm)	<ul style="list-style-type: none"> Column: 32.5 x 4.0 x 6.9 (825 x 102 x 172) Pole: 36.6 x 1.9 x 2.2 (929 x 48.5 x 55) Sub: 20.9 x 13.6 x 18.5 (530 x 345 x 471) Assembled: 80.5 x 13.6 x 18.5 (2045 x 345 x 471)
Net weight: lbs (kg)	<ul style="list-style-type: none"> Column: 10.34 (4.7) Pole: 2.75 (1.25) Sub: 44.66 (20.3) Total: 57.75 (26.25)
Power consumption	100-240 V AC, 50-60 Hz, 1.5-0.6 A