

A-NeuVideo ANI-16-4K60 16x16 UHD 4K/60Hz HDMI Matrix Switcher with Smart EDID Management

- **Inputs:** (16) HDMI Type A [19-pin female] / LAN [RJ45, Control] / RS-232 [9-pin D-sub, Control]
- **Outputs:** (16) HDMI Type A [19-pin female] / OLED display screen
- **HDMI Compliance:** HDMI 2.0b
- **HDCP Compliance:** HDCP 2.2 and HDCP 1.4
- **Video Bandwidth:** 10.2Gbps
- **Video Resolutions:** 4K2K@50/60Hz YUV4:2:0, 4K2K@30Hz YCbCr / YUV 4:4:4, 1080p@60Hz YCbCr4:4:4 / 4:2:2
- **Color Depth:** 8/10/12bit (1080p60Hz, YCbCr4:4:4) 8bit (4K60Hz, YUV 4:2:0)
- **Color Space:** YCbCr 4:4:4 / 4:2:2, YUV4:2:0
- **HDMI Audio Formats:** LPCM 7.1CH, Dolby TrueHD, Dolby Digital Plus and DTS HD Master Audio
- **ESD Protection Human Body Model:**
 - ± 8kV (air-gap discharge)
 - ± 4kV (contact discharge)
- **Housing:** Metal Enclosure
- **Color:** Black
- **Dimensions (WxDxH):** 19 x 12 x 1.75 in (440x303x44.5mm)
- **Weight:** 9.25 lb / 4.2 Kg
- **Power Supply:** 100~240VAC 50/60Hz
- **Power Consumption:** 31.3W
- **Operating Temperature:** 0°C ~ 40°C / 32°F ~ 104°F
- **Storage Temperature:** -20°C ~ 60°C / -4°F ~ 140°F
- **Relative Humidity:** 20~90% RH (non-condensing)