

A-NeuVideo ANI-16-4K60-S 16x16 UHD 4K/60Hz HDR HDMI Matrix Switcher with Down Scaler SPDIF Audio Extractor

- **HDMI Compliance:** HDMI 2.0b
- **HDCP Compliance:** HDCP 2.2/1.x
- **Video Bandwidth:** 18Gbps
- **Video Resolution:** Up to 4K2K@60Hz (4:4:4)
- **Color Space:** RGB, YCbCr 4:4:4/4:2:2/4:2:0
- **Color Depth:** 8-bit, 10-bit, 12-bit
- **HDMI Audio Formats (Pass-through):** LPCM 2/5.1/7.1, Dolby Digital, DTS 5.1, Dolby Digital+, Dolby TrueHD, DTS-HD Master Audio, Dolby Atmos, DTS:X
- **Coax Audio Formats:** LPCM 2.0, Dolby Digital / Plus, DTS 5.1
- **HDR Formats:** HDR10, HDR10+, Dolby Vision, HLG
- **ESD Protection Human Body Model:**
 - ± 8kV (air-gap discharge)
 - ± 4kV (contact discharge)
- **Input Ports:** (16) HDMI Type A [19-pin female]
- **Output Ports:**
 - (16) HDMI Type A [19-pin female]
 - (16) Coax Audio (RCA)
- **Control Ports:**
 - TCP/IP [RJ45]
 - RS-232 [D-Sub 9]
- **Housing:** Metal Enclosure
- **Color:** Black
- **Dimensions (WxDxH):** 19 x 7.9 x 1.7 in (440x200x44mm)
- **Weight:** 6.8lb / 3.1Kg
- **Power Supply:** Input: AC 100 - 240V 50/60Hz, Output: DC 24V/3.75A (US/EU standard, CE/FCC/ULcertified)
- **Power Consumption:** 76.8W
- **Operating Temperature:** -10°C ~ 45°C / 14°F ~ 113°F
- **Storage Temperature:** -20°C ~ 60°C / -4°F ~ 140°F
- **Relative Humidity:** 20~90% RH (non-condensing)