















- Intuitive User Interface
- Dynamically Renders Hive Cloud's Control Panels
- 10 Point Capacitive Touch
- PoE Powered
- Wall and Table Mounting Options
- Built-n Node

HIVE Touch is an Intuitive capacitive touch panel interface that seamlessly connects with HIVE Cloud. It renders HIVE's control panels natively to give a dynamic user experience. It provides access and asset management to the devices that are connected to the HIVE Cloud. HIVE Touch also emulates a software Node and acts as a control system for the entire room and control all IP devices in the room with no additional hardware. With built-in PoE and Wireless Connectivity HIVE Touch can be integrated into a wide range of applications.

Display	Size	10.1 Inch IPS
	Resolution	1280 x 800 WXGA
	Viewing Angle	±89° horizontal, ±89° vertical
	Luminance	300 nits cd/m2
	Contrast Ratio	800:1
	Touch	10 Point Capacitive Multi-Touch
System	CPU	Cortex-A17 Quad-core up to 1.6GHz
	RAM	2GB DDR
	Storage	8GB emmc
Connectivity	Ethernet	10/100BaseT
	WiFi	802.11a/b/g/n/ac
	Bluetooth	4.1
10	1x RJ45	PoE or PoE+ Supported
	1x USB	USB 2.0 Type A
Power	Supply	5V 4A DC (US/EU standards/ CE/FCC/UL certified)
	Consumption	32 Watt Max
Temperature	Operation	0~40°C [32~104°F]
	Storage	-20~60°C [-4~140°F]
	Relative Humidity	20~90% RH [No Condensation]
Mechanical	Mount	Table and Wall Mount
	Dimensions	6.60" x 10.24" x 1.53" (168 x 260 x 39 mm)
	Weight	24 oz (680 g)
	Housing	Aluminum
	ESD	Human body model - ±12kV [air-gap discharge] & ±8kV

