

Specifications for 48-Port Gb PoE+ L2 L3 Managed Switch w/ 4 SFP

Dimensions & Measurements

| | |
|-----------------------|---------------------------|
| Height | 4.44 cm (1.75 in) |
| Length | 44.2 cm (17.4 in) |
| Max Power Consumption | 899W @ 100VAC |
| Operating Temperature | 32° to 122°F (0° to 50°C) |
| PoE Power Budget | 740W |
| Product Weight | 5.62 kg (12.4 lbs) |
| Switching Capacity | 104 GBPS |
| Width | 37.46 cm (14.75 in) |

Characteristics & Features

| | |
|------------------|---|
| Connection Type | Wired |
| Layer Support | <ul style="list-style-type: none">• L2• L3 |
| Number of Ports | 48 |
| PoE Self Healing | Per Port Basis |
| Port Location | Front |
| Power Cord | <ul style="list-style-type: none">• AU Cord• EU Cord• UK Cord• US Cord |
| ProWatch Type | ProWatch Integrated |
| SFP Port Type | 4 x 1 Gigabit |
| Switch Type | <ul style="list-style-type: none">• Managed• PoE+ |
| VLAN Compliance | 802.1Q |

Certifications & Warranties

Certifications

- CE-LVD
 - FCC
 - IC
 - RoHS
 - VCCI
-