

Hall Technologies SW-HD-4A 4x1 HDMI Switcher/IR/RS-232/Telnet and Web GUI

Video Standards	Input: 4x HDMI 2.0 Output: 1x HDMI 2.0 Bandwidth 18 Gbps Video Resolutions Up to 4K60 (4:4:4) VGA (640x480) through WQXGA@30
Audio Standards	Connectors 3.5 mm Stereo Analog Optical SPDIF Digital (TOSLINK) Formats LPCM 2/5.1/7.1 CH, Dolby Digital 2-5.1 CH, DTS 2-5.1 CH, Dolby TrueHD and DTS-HD Master Audio
Other Signals	LAN 1 RJ45 RS-232: Baud Rate: 115200, N, 8, 1 USB-Mini For Firmware Updates Terminal Strip 1 RX, TX and GND
Controls	Front Panel Buttons, IR Remote Control (Included), Telnet, WebGUI
Included Accessories	12V DC Power Supply, IR Remote Control, IR Remote Detector Cable, Mounting Brackets (x2)
Environmental	Operating +32 to +122 °F (0 to +50 °C) Storage -40 to +158 °F (-40 to +70 °C) Humidity (RH) 10% to 90%, non-condensing
Dimensions (W x D x H)	7.96" (202 mm) W x 2.96" (75 mm) D x 1.15" (29 mm) H
Weight	0.95 lbs (0.43 kg)