

Kramer K-180MINI Panocam 4K 12 MP Camera/3 Lens 180-degree FOV Fixed Focus/2 Mic AI-Powered Auto Framing/Face Detection

PORTS

- 1 USB 2.0 type A: On a USB connector
- 1 USB-C 2.0: On a USB-C connector

VIDEO

- Output Formats: MJPG
- Output Formats: H.264
- Output Formats: YUY2
- Resolutions: YUY2 (30fps): 640x480, 640x360, 480x270, 352x288, 320x240
- Resolutions: MJPG (30fps): 3840x2160(24fps), 3840x1376, 3840x962, 2560x1440, 1920x1080, 1280x720, 1024x576, 960x544, 640x480, 640x360
- Resolutions: H264 (30fps): 1280x720, 1024x576, 960x544, 640x480, 640x360

FOCUS

- Method: : Fixed
- Distance: 1.5 meters

CAMERA

- Max. Field of View (FOV): 180
- Depth of Field (DOF): 0.5 to 5 meters
- Aperture: 2.2
- Minimum Illumination: 10Lux

MICROPHONE

- Quantity: 2
- Pickup Distance: Up to 4 meters

CONTROLS

- Top Button: Selectable layouts
- App: Layout configuration via PC

POWER

- Consumption: 5V/950mA 4.7W

ENVIRONMENTAL CONDITIONS

- Operating Temperature: 0° to +40°C (32° to 104°F)
- Storage Temperature: -20° to +60°C (-4° to 140°F)
- Humidity: 10% to 90%, RHL non-condensing
- Altitude: Below 5000 meters

REGULATORY COMPLIANCE (STANDARDS COMPLIANCE)

- Safety: CE, FCC
- Environmental: RoHS, WEEE

ENCLOSURE

- Type: Aluminum

GENERAL

- Net Dimensions (W, D, H): 14.7cm x 7.4cm x 3.5cm (5.8" x 2.9" x 1.4")
- Shipping Dimensions (W, D, H): 17.6cm x 17.6cm x 4.6cm (6.9" x 6.9" x 1.8")
- Net Weight: 0.24kg (0.53lbs) approx
- Shipping Weight: 0.59kg (1.3lbs) approx

ACCESSORIES

- Included: 1 USB-C cable, wall bracket, and screws set