

Panel	Panel Type:	LED-Backlit TFT LCD (TN Technology)
	Panel Size:	19.0"
	Max. Resolution:	SXGA 1280 x 1024
	Pixel Pitch:	0.294 mm
	Brightness:	250 cd/m ²
	Contrast Ratio:	20,000,000:1 (DCR)
	Viewing Angle (H/V):	170°/160°
	Display Colour:	16.7M
	Response Time:	3 ms
Frequency	Frequency (H):	24 kHz-83 kHz
	Frequency (V):	50 Hz-75 Hz
Signal Input	DisplayPort:	x 1
	HDMI:	1.4 x 1
	DVI:	24-Pin DVI-D
	VGA:	15-Pin D-Sub x 1
	Composite:	BNC x 2
	S-Video:	4-Pin mini DIN x 1
Signal Output	Composite:	BNC x 2
External Control	RS232 In:	2.5 mm Phone Jack
Other Connectivity	USB:	2.0 x 1 (Service Port)
Audio	Audio In:	Stereo Audio Jack (3.5 mm), Stereo Audio Jack (RCA)
	Audio Out:	Stereo Audio Jack (RCA)
	Internal Speakers:	2W x 2
Power	Power Requirements:	DC 12V, 1.75A
	On Mode:	16W (On)
	Standby Mode:	< 0.5W
	Off Mode:	< 0.3W
Glass	Thickness:	3.0 mm (0.12")
	Reflection Rate:	< 1%
	Transmission Rate:	> 97%
	Hardness:	> 9H
Operating Conditions	Temperature:	0°C-40°C (32°F-104°F)
	Humidity:	10%-90% (non-condensing)
Mounting	VESA FPMPMI:	Yes (100 x 100 mm & 75 x 75 mm)
Stand	Tilt:	0° to 22°
Security	Kensington Security Slot:	Yes

Dimensions	Product with Base (W x H x D):	445.4 x 420.2 x 175.0 mm (17.5" x 16.5" x 6.9")
	Product w/o Base (W x H x D):	445.4 x 383.9 x 64.5 mm (17.5" x 15.1" x 2.5")
	Packaging (W x H x D):	552.0 x 526.0 x 225.0 mm (21.7" x 20.7" x 8.9")
Weight	Product w/o Base:	6.1 kg(13.4 lb)
	Product with Base:	6.9 kg(15.2 lb)
	Packaging:	9.3kg (20.5 lb)
Regulation Approval	Certifications & Compliance:	CB, CE, FCC,BSMI, CCC, RoHS, WEEE, REACH, UKCA, ICES-003 (Issue 7)
Accessories	Supplied:	Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card
Optional Accessories	Ceiling Mount (Landscape only):	CMP-01+WMK-03
	Wall Mount (Landscape only):	WMA-01, WMK-01, WMK-03, PMK-01
	Desk mount (Landscape only):	DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02
Power	Power Supply:	External
Storage Conditions	Temperature:	-20°C-60°C (-4°F-140°F)
	Humidity:	5%-95% (non-condensing)