

Key Digital KD-MLV4x4Pro 4x4 4K UHD HDMI Seamless Matrix with Multi-View Tiling with 4 Rx Units

Technical:

- **Input (Each):** 1 HDMI Connector, Type A, 19 Pin Female
- **Output (Each):** 1 HDMI Connector, Type A, 19 Pin Female
- **Output (Each):** Balanced/unbalanced line level audio on 6-pin terminal block. Drives 2VRMS line audio input with a sampling rate of 192KHz
- **Output (each):** Toslink optical digital audio following SPDIF format (IEC 60958). Supports sampling rate up to 192KHz
- **Video Bandwidth:** TMDS bandwidth 10.2 Gbps
- **DDC Signal (Data):** Input DDC Signal - 5 Volts p-p (TTL)
- **HDMI Video/Audio Signal:** Input Video Signal - 1.2 Volts p-p
- **DDC Communication:** EDID and HDCP Bi-directional buffering to Display and Source
- **Analog Audio Max Output Level:** 4dBu on 150k Ω , DC coupling
- **Audio Bandwidth:** 20Hz to 20kHz @ 0dBu
- **TND + Noise:** 0.33% @0dBu @ 1kHz
- **Optical Max Output Level:** 1Vpp on 75 Ω , DC coupling
- **Wired IR:** modulated IR signal input, 0-5V TTL or -10 to +10V
- **Power:** 12V/5A (60W) AC Power Supply with Grounded, 2.1mm ID DC Power Jack with Screw In Type

General:

- **Regulation:** CE, RoHS, WEEE
- **Rack Mount:** 1U, 1 Rack Width (rack ears included)
- **Enclosure:** Black Metal
- **KD-MS4x4G Dimensions:** L = 17.24" W = 10.78" H = 1.73" (438 x 237.7 x 44mm)
- **Shipping Carton Dimensions:** L = 19.69" W = 14.72" H = 5.12" (500 x 374 x 130mm)
- **Product Weight:** 8.02 lb / 3.64 kg
- **Shipping Weight:** 13.93 lb / 6.32 kg
- **Accessories:** IR Remote, UL Certified Power Supply