

|                            |  |                      |
|----------------------------|--|----------------------|
| Image Sensor               | Sensor   | 1/2.7" HD color CMOS |
|                            | Effective pixel  | 2.1 mega pixel       |
|                            | Min. illumination  | 0.5Lux at F2.0       |
|                            | White Balance  | Auto/manual          |
|                            | Gain control   | Auto                 |
|                            | Backlight compensation   | On/Off               |
|                            | SN ratio   | >50db                |
| Lens                       | Focal length   | 4mm                  |
|                            | Aperture   | Auto/manual          |
|                            | zoom   | Fixed focus          |
|                            | Horizontal view angle  | 72.5°                |
| Video output               | USB2.0   |                      |
| Signal system              | 1080P30, 720P25  |                      |
| Control terminal           | USB, RS-232C, RS-485(Bidirectional)  |                      |
| Control Protocol           | VISCA, PELCO-D   |                      |
| Baud rate                  | 9600/38400bps  |                      |
| Patrol line                | 4 cruise sequence  |                      |
| Preset position            | 64 preset positions  |                      |
| Image flip                 | Support Horizontal/Vertical image flip   |                      |
| Pan movement speed         | 1-280°/S   |                      |
| Tilt movement speed        | 1-100°/S   |                      |
| Pan movement range         | 355°Continuously rotate  |                      |
| Tilt movement range        | Up: 90°, Down: 45°   |                      |
| Pan scanning automatically | Support  |                      |
| Boundary scanning          | 0-359° scanning (programmable)   |                      |
| Remote controller          | IR Wireless Remote controller P/T  |                      |
| Power supply               | DC12V±10%,1.2A   |                      |
| Work Temperature           | 0-50   |                      |
| Work Humidity              | 0-95% RH   |                      |
| Accessories                | DC 12Vpower adaptor, IR remote control, manual, USB2.0 cable(5m),Brackets & screws |                      |
| Color                      | Black  |                      |
| Dimension(LXWXH)           | 125mm×120mm×145mm/220mm x 180mm x 225mm(before/after packing)                      |                      |
| Weight                     | 640g /1.38kg(before/after packing)   |                      |