

**Aten PE0116SA Basic PDU with Surge Protection/100-120 VAC/15A Max**

Function	PE0116SA	PE0116SG
<b>Electrical</b>		
Nominal Input Voltage	100-120 VAC	100-240 VAC
Maximum Input Current	15A Max (UL de-rated 12A Max) (PSE 10A)	10A Max
Input Frequency	50-60 Hz	50-60 Hz
Input Connection	NEMA 5-15P	IEC-320 C14
Input Power	1800VA(Max); 1440VA(UL de-rated)	2400VA(Max)
Outlet Type	(16) NEMA 5-15R	(16) IEC 320 C13
Maximum Output Current (Outlet)	15A Max (UL de-rated 12A Max) (PSE 10A)	10A Max
Maximum Output Current (Bank)	15A Max (UL de-rated 12A Max) (PSE 10A)	10A Max
Maximum Output Current (Total)	15A Max (UL de-rated 12A Max) (PSE 10A)	10A Max
OPD(Overcurrent Protection Device)	Yes	Yes
<b>Physical Properties</b>		
Dimensions (L x W x H)	71.56 x 4.44 x 6.00 cm (28.17 x 1.75 x 2.36 in.)	71.56 x 4.44 x 6.00 cm (28.17 x 1.75 x 2.36 in.)
Weight	1.10 kg ( 2.42 lb )	1.10 kg ( 2.42 lb )
Power Cord Length	10ft(14#)	10ft(3×1.0mm2)
<b>Environmental</b>		
Temperature (Operating / Storage)	0 - 40°C / -20 - 60°C	0 - 40°C / -20 - 60°C
Elevation (Operating / Storage)	3000m	3000m
<b>Compliance</b>		
EMC Verification	FCC Class A	CE Class A
Safety Verification	By Request	CE,LVD
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.	