

Aten PE0224SA Basic PDU with Surge Protection/100-120 VAC/20A Max

Function	PE0224SA	PE0224SB	PE0224SG
Electrical			
Nominal Input Voltage	100-120 VAC	100-240 VAC	100-240 VAC
Maximum Input Current	20A Max (UL de-dated 16A Max)	20A Max (UL de-dated 16A Max)	16A Max
Input Frequency	50-60 Hz	50-60 Hz	50-60 Hz
Input Connection	For A plug: NEMA L5-20P For A2 plug: NEMA 5-20P	NEMA L6-20P	IEC-320 C20
Input Power	2400VA(Max); 1920VA(UL de-rated)	4800VA(Max); 3840VA(UL de-rated)	3840VA(Max)
Outlet Type	(24) NEMA 5-20R	(22) IEC 320 C13, (2) IEC 320 C19	(22) IEC 320 C13, (2) IEC 320 C19
Maximum Output Current (Outlet)	20 Max (UL de-dated 16A Max)	C19: 20A Max (UL de-dated 16A Max) C13: 15A Max (UL de-dated 12A Max)	C13: 10A Max C19: 16A Max
Maximum Output Current (Bank)	20A Max (UL de-dated 16A Max)	20A Max (UL de-dated 16A Max)	16A Max
Maximum Output Current (Total)	20A Max (UL de-dated 16A Max)	20A Max (UL de-dated 16A Max)	16A Max
OPD(Overcurrent Protection Device)	Yes	Yes	Yes
Physical Properties			
Dimensions (L x W x H)	96.68 x 4.44 x 6.00 cm (38.06 x 1.75 x 2.36 in.)	96.68 x 4.44 x 6.00 cm (38.06 x 1.75 x 2.36 in.)	96.68 x 4.44 x 6.00 cm (38.06 x 1.75 x 2.36 in.)
Weight	1.40 kg (3.08 lb)	1.40 kg (3.08 lb)	1.40 kg (3.08 lb)
Power Cord Length	10ft(12#)	10ft(12#)	10ft(3×1.5mm2)
Environmental			
Temperature (Operating / Storage)	0 - 40°C / -20 - 60°C	0 - 40°C / -20 - 60°C	0 - 40°C / -20 - 60°C
Elevation (Operating / Storage)	3000m	3000m	3000m
Compliance			
EMC Verification	FCC Class A	FCC Class A	CE Class A
Safety Verification	By Request	By Request	CE,LVD
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.		