

## Hollyland HL-Solidcom C1-3S Full-Duplex Wireless DECT Intercom System with 3 Headsets (1.9 GHz)

Number of Included Headsets	<b>3 x</b> Single-Sided Headset
Wireless Technology	Digital DECT (1.9 GHz)
DECT Standard	6.0
Operating Range	1000' / 304.8 m
Users per System	3
Wireless Modulation	<b>Analog:</b> GFSK
Duplex Mode	Echo Cancellation
Approximate RF Sensitivity	-90 dBm
Encryption	Proprietary
Earpiece Design	On-Ear (Supra-Aural) / Over-Ear (Circumaural)
Earpiece Connection / Wearing Style	Headband
Number of Earpieces	Single Earpiece (Left or Right Side)
Sound Field	Mono
Controls/Microphone Location	Controls: Adjustable Boom, Earpiece (Side Unspecified)
Frequency Response	150 Hz to 7 kHz
Maximum Sound Pressure Level (SPL)	115 dB
Total Harmonic Distortion (THD)	1%
SNR	<b>Headphones:</b> >55 dB
Type	Electret Condenser
Mic Boom Location	Interchangeable (Left or Right Side)
Pickup Pattern	Cardioid (Unidirectional)
Maximum SPL	115 dB
Distortion	<1%
Audio Connector to Source	<i>None</i>
Battery Type	<b>Headset:</b> <b>1 x</b> 26650
Battery Chemistry	<b>Headset:</b> Lithium-Ion
Capacity (mAh)	700 mAh
Runtime	<b>Headset:</b> 10 Hours
Recharge Time	2.5 Hours
Operating Temperature	32 to 113°F / 0 to 45°C
Storage Temperature	-4 to 140°F / -20 to 60°C
Water Resistance	<i>None</i>
IP Rating	<i>None</i>
Package Weight	3.58 lb
Box Dimensions (LxWxH)	9.5 x 8.7 x 7.5"