

PreSonus Eris E5 XT 2-Way 5.25 inch Near Field Studio Monitor with EBM Waveguide

Inputs	1- Balanced XLR
	1- Balanced ¼" TRS
	1- Unbalanced RCA
Performance	
Frequency Response	48 Hz - 20 kHz
Crossover Frequency	3 kHz
LF Amplifier Power	45W
HF Amplifier Power	35W
Peak SPL (@ 1 meter)	102 dB
LF Driver	5.25"
HF Driver	1" silk dome
Input Impedance	10 kΩ
Dispersion	100 degrees horizontal by 60 degrees vertical
User Controls	
Volume Range	A-type taper
MF Control	-6, 0, +6 dB
HF Control	-6, 0, +6 dB
Low Cut	Flat, 80 Hz, or 100 Hz
Acoustic Space	Flat, -2 dB, or -4 dB
Protection	RF interference
	Output-current limiting
	Over-temperature
	Turn-on/off transient
	Subsonic filter
	External mains fuse
Power	100-120V ~50/60 Hz or 220-240V ~50/60 Hz
Cabinet	Vinyl-laminated, medium-density fiberboard
Physical	
Width	8" (203.2 mm)
Depth	9" (228.6 mm)
Height	11" (279.4 mm)
Weight	11 lbs (4.99 kg)