

BZBGEAR BG-EXUF 4-Port USB3.1/2.0/1.1 SuperSpeed Fiber Extender up to 1000ft

Distance	
USB 3.1 Gen1	Single-mode fiber or OM3 multi-mode fiber: Non-real-time transmission: 984ft (300m) Real-time transmission: 328ft (100m)
USB 2.0/1.1	Single-mode fiber: Non-real-time transmission: 6.2mi (10km) Real-time transmission: 3.7mi (6km) OM3 multi-mode fiber: 1640ft (500m)
Data Rate	
USB 3.1 GEN1	5Gbps
USB 2.0	480Mbps
USB 1.1	12Mbps
Transmitter (BG-EXUF-TX)	
USB Interface	1x USB 3.0 type-B male connector
Fiber Interface	1x LC
Dimensions	135mm x 75mm x 26mm
Installation	4 mounting holes for fixing
Enclosure Material:	Metal
Power Supply	External DC 12V
Receiver (BG-EXUF-RX)	
USB Interface	4x USB 3.0 type-A female connector
Fiber Interface	1x LC
Dimensions	160mm x 85mm x 26mm
Installation	4 mounting holes for fixing
Enclosure Material:	Metal
Power Supply	External DC 12V
Environment	
Operating Temperature	+50 to +140°F / -10 to +60°C
Storage Temperature	-49 to +185°F / -45 to +85°C
Operating Humidity	20% to 80% relative humidity, non-condensing
Storage Humidity	10% to 80% relative humidity