

## AG Neovo PD-43Q PD-Series 43 inch Class 4K UHD LED Commercial Display

Panel	Panel Type:	LED-Backlit TFT LCD (IPS Technology)
	Panel Size:	42.5"
	Max. Resolution:	UHD 3840 x 2160
	Pixel Pitch:	0.245 mm
	Brightness:	700 cd/m <sup>2</sup>
	Contrast Ratio:	1200:1
	Viewing Angle (H/V):	178°/178°
	Display Colour:	1.07G
	Response Time:	5 ms
	Surface Treatment:	Anti-glare treatment (Haze 25%),3H Hard Coating
Frequency	Frequency (H):	31 kHz-92 kHz
	Frequency (V):	48 Hz-85 Hz
Signal Input	DisplayPort:	x 1
	HDMI:	2.0 x 3
	DVI:	29-Pin DVI-I x 1 (VGA)
Signal Output	DisplayPort:	1
External Control	IR In:	3.5 mm Phone Jack
	IR Out:	3.5 mm Phone Jack
	RS232 In:	2.5 mm Phone Jack
	RS232 Out:	2.5 mm Phone Jack
	LAN:	RJ45 x 1
Other Connectivity	USB:	2.0 x 1 (Service Port / Media Playback) / 2.0 x 1 (Media Playback)
	Micro SD Card Slot:	Yes
Audio	Audio In:	Stereo Audio Jack (3.5 mm)
	Audio Out:	Stereo Audio Jack (3.5 mm)
	Internal Speakers:	10W x 2
Power	Power Requirements:	AC 100-240V, 50/60 Hz
	On Mode:	123W (On)
	Standby Mode:	< 0.5W
	Off Mode:	0W
Operating Conditions	Temperature:	0°C-40°C (32°F-104°F)
	Humidity:	20%-80% (non-condensing)
Mounting	VESA FPMPI:	Yes (200 x 200 mm)
Security	Kensington Security Slot:	Yes
Dimensions	Product w/o Base (W x H x D):	973.0 x 561.2 x 63.5 mm (38.3" x 22.1" x 2.5")
	Packaging (W x H x D):	1070.0 x 680.0 x 141.0 mm (42.1" x 26.8" x 5.6")
Weight	Product w/o Base:	10.7 kg (23.6 lb)
	Packaging:	13.1 kg (28.9 lb)
Regulation Approval	Certifications & Compliance:	FCC, CE, LVD, ICES-003(Issue 7), WEEE, RoHS, REACH
Accessories	Supplied:	Power Cord, HDMI Cable, Remote Control, Batteries, Quick Start Guide
Optional Accessories	Floor Mount:	FMS-01, FMS-02, FMC-02
	Ceiling Mount:	CMP-01+LMK-02, CMP-01+WMK-03
	Video Wall Mount:	VWM-01, VWM-02
	Wall Mount:	LMA-01, WMA-01, LMK-02, WMK-03
	Desk Mount:	DTS-01
	Ceiling Mount (Landscape only):	CMP-01+LMK-01
	Wall Mount (Landscape only):	LMK-01, LMK-03, LMA-02
Other Connectivity	SDM Slot:	SDM-S
Power	Power Supply:	Internal
Storage Conditions	Temperature:	-20°C-60°C (-4°F-140°F)

Humidity:

10%-90%(non-condensing)